



## BNC CONNECTORS



✓ Active

↓ **PRODUCT DRAWING**  
English

↓ **3D PDF**

TE CONNECTIVITY (TE)

### JACK ASSY,RTANG,BNC

5413879-1

TE Internal Number: 5413879-1

Always EU RoHS/ELV Compliant

Applies To **Panel, Printed Circuit Board**

Panel Mount Retention **With**

Panel Mount Retention Type **Lockwasher and Nut**

PCB Mount Retention **With**

PCB Termination Method **Hold-Down Posts**

#### Product Drawings

[JACK, RIGHT ANGLE, PCB 50 OHM, SERIES BNC](#)

PDF  
English

#### CAD Files

[Customer View Model](#)

3D\_IGS.ZIP  
English

[Customer View Model](#)

3D\_STP.ZIP  
English

[Customer View Model](#)

2D\_DXF.ZIP  
English

[3D PDF](#)

PDF  
English

#### Catalog Pages/Data Sheets

[BNC Connectors](#)

PDF  
English

[1-1773725-8\\_RF\\_COAX\\_QRG](#)

PDF  
English

#### Product Environmental Compliance

TE Material Declaration

[MD\\_5413879-1\\_011220162310\\_dmtec](#)

PDF  
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

	Sealed	<b>No</b>
	RF Connector Type	<b>BNC</b>
	Connector Style	<b>Jack</b>
	PCB Mounting Orientation	<b>Right Angle</b>
	Dielectric Material	<b>Polymethylpentene</b>
	ESD Protection	<b>Without</b>
	Isolated Ground	<b>No</b>
	Grade	<b>Commercial</b>
	Product Type	<b>Connector - RF</b>
<hr/>		
Configuration Features	Solder Terminal	<b>Without</b>
	Number of Ports	<b>1</b>
<hr/>		
Electrical Characteristics	50 Ohm	<b>Yes</b>
	75 Ohm	<b>No</b>
	Impedance ( $\Omega$ )	<b>50</b>
<hr/>		
Body Features	Body Material	<b>Zinc</b>
	Body Plating Material	<b>Nickel</b>
	Body Style	<b>Right Angle</b>
	Body Insulation	<b>Without</b>
	Body Shape	<b>Right Angle</b>
<hr/>		
Contact Features	Center Contact Material	<b>Phosphor Bronze</b>
	Center Contact Plating Material	<b>Gold</b>
	Center Contact Plating Thickness ( $\mu\text{in}$ )	<b>30</b>
<hr/>		
Termination Features	PCB Termination Method	<b>Hold-Down Posts</b>
<hr/>		
Mechanical Attachment	Panel Mount Retention	<b>With</b>
	Panel Mount Retention Type	<b>Lockwasher and Nut</b>
	PCB Mount Retention	<b>With</b>
	Panel Mount	<b>With</b>
	Polarized	<b>No</b>
	Mounting Post Length	<b>3.48 mm [ .137 in ]</b>
	Mounting Post Style	<b>Standard</b>

Panel Attachment Style

**Rear Mount**

Hardware Included

**No**

Dimensions

Height above PCB

**12.7 mm [ .5 in ]**

Packaging Features

Packaging Method

**Tube**

Other

Comment





**If an Insulating Bushing is required, see Part Number 330620.**

Product Compliance

[Statement of Compliance](#)  
PDF

[VIEW ALL PRODUCT COMPLIANCE](#)

## CUSTOMERS ALSO BOUGHT

WIRE-TO-BOARD CONNECTOR CONTACTS	SURFACE MOUNT RESISTORS	SMB CONNECTORS	SMB CONNECTORS
			
<b>.045 POST CONTACT AUPLBR</b> 350980-3	<b>RN 0805 6R04 0.1% 10PPM 1K RL</b> RN73C2A6R04BTDF	<b>PLUG, CABLE, RTANG, SMB, PB FREE</b> 5414363-4	<b>5162 5013 09, SMB PCB JACK RECP</b> 1060455-1
<a href="#">Save to List</a> <a href="#">Find Similar Products</a>	<a href="#">Save to List</a> <a href="#">Find Similar Products</a>	<a href="#">Save to List</a> <a href="#">Find Similar Products</a>	<a href="#">Save to List</a> <a href="#">Find Similar Products</a>