



TE Connectivity: Every Connection Counts  
© 2015 TE Connectivity Ltd. family of companies. All Rights Reserved

HEAT SHRINK TUBING



TE CONNECTIVITY (TE)  
**ATUM-9/3-0-STK**

[Raychem](#) | [ATUM](#)

ATUM-9/3-0-STK

TE Internal Number: 5507832055

Alias ID: 7-1194346-7

[EU RoHS Compliant](#)

[EU ELV Compliant](#)

Wall Type **Dual**

Resistant To **Fluids, Mechanical Damage, Strain**

Low Outgassing **No**

Product Source **Czech Republic, US**

Packaging Method **Stick**



✓ Active



[Catalog Pages/Data Sheets](#)

[ATUM Pages From 9-1773447-9](#)

PDF

English

[Product Specifications](#)

## Product Specification

[ATUM Sleeving \(Black\)](#)

PDF

**English**

## Product Environmental Compliance

## TE Material Declaration

[MD\\_5507832055\\_03182012228](#)

PDF

**English**

## Instruction Sheets

## Instruction Sheet (U.S.)

[Global Dimensional Life For RAYCHEM Heat Shrink Tubing Standard Size Products \(Customer Distribution\)](#)

PDF

**English**Please review product documents or [contact us](#) for the latest agency approval information.

## Product Type Features

Wall Type

**Dual**

Product Family

**ATUM**

## Electrical Characteristics

Voltage (Max) (kV)

**.6**

## Body Features

Shrink Ratio

**3:1**

Color

**Black**

Flexibility	<b>Semi-Flexible</b>
Material	<b>Irradiated Modified Polyolefin</b>
Fluid Type	<b>Chemicals/Solvents, Diesel Fuel, Hydraulic Fluid, Lubricating Oil, Water</b>

---

**Dimensions**

Expanded Inside Diameter (Min)	<b>9 mm [ .354 in ]</b>
Recovered Inside Diameter (Max)	<b>3 mm [ .118 in ]</b>
Recovered Wall Thickness (Tolerance)	<b>.28 mm [ .011 in ]</b>
Recovered Wall Thickness (Nominal)	<b>1.4 mm [ .055 in ]</b>
Cut Length	<b>1220 mm [ 48.031 in ]</b>




---

**Usage Conditions**

Resistant To	<b>Fluids, Mechanical Damage, Strain</b>
Recovery Temperature (°C)	<b>110</b>
Operating Temperature Range (°C)	<b>-55 – 110</b>
Flammability	<b>Flame-Retardant</b>
Shrink Temperature (Min) (°C)	<b>80</b>
Fluid Resistance	<b>Moisture, Splash Protection, Spray Protection</b>

---

**Product Availability**
**Applicable Region**
**Global**

Packaging Features

Packaging Method

**Stick**

Other

Low Outgassing

**No**

Product Source

**Czech Republic, US**

Statement of Compliance

[Statement of Compliance](#)

PDF



## Customers Also Bought

HEAT SHRINK TUBING



**ATUM-6/2-0-STK**  
ATUM-6/2-0-STK

HEAT SHRINK TUBING



**ATUM-12/4-0-STK**  
ATUM-12/4-0-STK

HEAT SHRINK TUBING



**ATUM-9/3-0-75MM**  
ATUM-9/3-0-75MM

THROUGH-HOLE RESISTORS



**C10 330R 5% (LOOSE)**  
C10330RJL

