



RJ14 CONNECTORS



Active

PRODUCT DRAWING
English

3D PDF

TE CONNECTIVITY (TE)

MJ,TE,6P/4C,PNL STOPS,TRAY P

TE, TE-MA

5520258-2

TE Internal Number: 5520258-2

Always EU RoHS/ELV Compliant

Port Configuration **Single**

Jack Configuration **1 x 1**

Connector Style **Jack**

Inverted Jack Face **No**

Profile **Low**

Product Drawings

[MODULAR JACK ASSEMBLY, TOP ENTRY, 6 POSITION, FLANGELESS, WITH PANEL STOPS](#)

PDF
English

CAD Files

[3D PDF](#)

PDF
English

[Customer View Model](#)

2D_DXF.ZIP
English

[Customer View Model](#)

3D_IGS.ZIP
English

[Customer View Model](#)

3D_STP.ZIP
English

Catalog Pages/Data Sheets

[1-1773464-9_MODULAR JACKS_SINGLE_PORT_PCB_MOUNT](#)

PDF
English

Product Specifications

Product Specification

[Modular Plugs, Thru-Hole And Surface Mount Jacks, Data And Telephone, PCB Mounted](#)

PDF
English

Application Specification

[Modular Jacks](#)

PDF
English

Product Environmental Compliance

TE Material Declaration

[MD_5520258-2_10282014320_dmtec](#)

PDF
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features	Connector Style	Jack
	Profile	Low
	PCB Mounting Orientation	Top Entry (Vertical)
	Shielded	No
	LED	Without
	Jack Type	RJ14
	Panel Stops	With
	Performance Category	Cat 3
	Latch Style	Standard
	Product Type	Connector
Grounding Options	Without	

Configuration Features	Port Configuration	Single
	Jack Configuration	1 x 1
	Keyed	No
	Number of Positions	6

Body Features	Inverted Jack Face	No
	Color	Black

Contact Features	Contact Base Material	Phosphor Bronze
	Number of Contacts Loaded	4
	Contact Mating Area Plating Thickness (µm)	1.27
	Solder Tail Contact Plating Material	Tin over Nickel
	Contact Mating Area Plating Material	Gold

Mechanical Attachment	PCB Mounting Style	Through Hole
	Flanged	No
	Panel Mount Retention	With

Housing Features	Housing Material	PBT Polyester
------------------	------------------	----------------------

Dimensions	Height	16.5 mm [.65 in]
	PCB Thickness (Recommended)	1.57 mm [.062 in]

PCB Tail Length

3.18 mm [.125 in]

Industry Standards

UL Flammability Rating

UL 94V-0

Packaging Features

Packaging Quantity

2304

Packaging Method

Package, Tray, Tray/Box

Product Compliance

[Statement of Compliance](#)
PDF

[VIEW ALL PRODUCT COMPLIANCE](#)