



RJ25 CONNECTORS



✓ Active

↓ **PRODUCT DRAWING**
English

↓ **3D PDF**

TE CONNECTIVITY (TE)

MJ,R/A,6P,PNL,RH LTCH,GRY

AMP-LATCH

5555003-1

TE Internal Number: 5555003-1

Always EU RoHS/ELV Compliant

Port Configuration **Single**

Jack Configuration **1 x 1**

Connector Style **Jack**

Inverted Jack Face **No**

Profile **Standard**

Product Drawings

MODULAR JACK ASSEMBLY, SIDE ENTRY, WITH RIGHT HAND LATCHES, 6 POSITION, FLANGELESS, WITH PANEL STOPS

PDF (TIFF AVAILABLE)
English

MODULAR JACK ASSEMBLY, SIDE ENTRY, WITH RIGHT HAND LATCHES, 6 POSITION, FLANGELESS, WITH PANEL STOPS

PDF (TIFF AVAILABLE)
English

CAD Files

3D PDF

PDF
English

Customer View Model

2D_DXF.ZIP
English

Customer View Model

3D_IGS.ZIP
English

Customer View Model

3D_STP.ZIP
English

Catalog Pages/Data Sheets

82066 - Modular Jacks And MRJ21 Product Catalog - Single Port Modular Jacks Section

PDF
English

1-1773464-9_MODULAR_JACKS_SINGLE_PORT_PCB_MOUNT

PDF
English

Product Specifications

Product Specification

Modular Plugs, Thru-Hole And Surface Mount Jacks, Data And Telephone, PCB Mounted

PDF
English

Application Specification

Modular Jacks

PDF
English

Product Environmental Compliance

TE Material Declaration

[MD_5555003-1_12122015031_dmtec](#)
PDF
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features	Connector Style	Jack
	Profile	Standard
	PCB Mounting Orientation	Side Entry (Right Angle)
	Shielded	No
	Panel Stops	With
	Latch Style	Offset
	Performance Category	Cat 3
	Jack Type	RJ25
	Product Type	Connector
	Grounding Options	Without
	Applies To	Panel
	LED	Without
	Connector Type	Connector Assembly
Configuration Features	Port Configuration	Single
	Jack Configuration	1 x 1
	Preloaded	Yes
	Keyed	Yes
	Number of Positions	6
Body Features	Inverted Jack Face	No
	Color	Gray
Contact Features	Contact Base Material	Phosphor Bronze
	Solder Tail Contact Plating Material	Tin over Nickel
	Contact Mating Area Plating Material	Gold
	Contact Mating Area Plating Thickness (µin)	50
	Number of Contacts Loaded	6

Termination Features	Termination Method to PC Board	Solder
Mechanical Attachment	PCB Mounting Style	Through Hole
	Panel Mount Retention	With
	Flanged	No
Housing Features	Housing Color	Gray
	Housing Material	PBT
Dimensions	PCB Thickness (Recommended)	1.57 mm [.062 in]
	Height	16.13 mm [.635 in]
	PCB Tail Length	3.8 mm [.15 in]
Industry Standards	UL Flammability Rating	UL 94V-0
Packaging Features	Packaging Method	Package, Tray/Box
	Packaging Quantity	152
Product Compliance	Statement of Compliance PDF VIEW ALL PRODUCT COMPLIANCE	

CUSTOMERS ALSO BOUGHT

BOARD-TO-BOARD HEADERS & RECEPTACLES

2X 4P HV190FEDERLEI
216604-4

Save to List

Find Similar Products

STANDARD RECTANGULAR CONNECTORS

TC-ZIF HDR ASSY 260P
SHIELD FINGER
6565199-2

Save to List

Find Similar Products

SURFACE MOUNT RESISTORS

CPF 0402 243R 0.1%
25PPM 1K RL
CPF0402B243RE1

Save to List

Find Similar Products

SURFACE MOUNT RESISTORS

CPF 0402 22K 0.1% 25PPM
1K RL
CPF0402B22KE1

Save to List

Find Similar Products