



RJ25 CONNECTORS



Active

PRODUCT DRAWING
English

3D PDF

TE CONNECTIVITY (TE)

MJ,LPF,R/A,6P/6C,SMT,PNL STOP

Mini PCI

5555077-1

TE Internal Number: 5555077-1

Always EU RoHS/ELV Compliant

Port Configuration **Single**

Jack Configuration **1 x 1**

Connector Style **Jack**

Inverted Jack Face **No**

Profile **Low**

Product Drawings

[MODULAR JACK ASSEMBLY, 6 POSITION, LOW PROFILE, RIGHT ANGLE, SURFACE MOUNT W/ PANEL STOPS](#)

PDF
English

CAD Files

[Customer View Model](#)

2D_DXF.ZIP
English

[Customer View Model](#)

3D_IGS.ZIP
English

[Customer View Model](#)

3D_STP.ZIP
English

[3D PDF](#)

PDF
English

Catalog Pages/Data Sheets

[82066 - Modular Jacks And MRJ21 Product Catalog - Single Port Modular Jacks Section](#)

PDF
English

[1-1773464-9_MODULAR_JACKS_SINGLE_PORT_PCB_MOUNT](#)

PDF
English

Product Specifications

Product Specification

[Modular Plugs, Thru-Hole And Surface Mount Jacks, Data And Telephone, PCB Mounted](#)

PDF
English

Application Specification

[Modular Jack Surface Mount Printed Circuit \(PC\) Board Assemblies](#)

PDF
English

Product Type Features	Connector Style	Jack
	Profile	Low
	PCB Mounting Orientation	Side Entry (Right Angle)
	Shielded	No
	Panel Stops	With
	Latch Style	Standard
	Performance Category	Cat 3
	Jack Type	RJ25
	Product Type	Connector
	Grounding Options	Without
	Applies To	Panel
	LED	Without
	Connector Type	Connector Assembly

Configuration Features	Port Configuration	Single
	Jack Configuration	1 x 1
	Preloaded	Yes
	Keyed	No
	Number of Positions	6

Body Features	Inverted Jack Face	No
	Color	Black





Contact Features	Contact Base Material	Phosphor Bronze
	Solder Tail Contact Plating Material	Tin over Nickel
	Contact Mating Area Plating Material	Gold
	Contact Mating Area Plating Thickness (µin)	50
	Number of Contacts Loaded	6

Termination Features	Termination Method to PC Board	Solder
----------------------	--------------------------------	---------------

Mechanical Attachment	PCB Mounting Style	Surface Mount
	Panel Mount Retention	With
	Flanged	No

Housing Features	Housing Color	Black
	Housing Material	High Temperature Nylon
Dimensions	PCB Thickness (Recommended)	1.57 mm [.062 in]
	Height	12.7 mm [.5 in]
Industry Standards	UL Flammability Rating	UL 94V-0
Packaging Features	Packaging Method	Package, Tray/Box
	Packaging Quantity	152
Product Compliance	Statement of Compliance PDF VIEW ALL PRODUCT COMPLIANCE	

CUSTOMERS ALSO BOUGHT

<p>RJ14 CONNECTORS</p>  <p>MJ, LPF, R/A, 6P/4C, SMT, PNL STOP 5555077-2</p> <p>Save to List Find Similar Products</p>	<p>RECTANGULAR CONNECTOR HARDWARE</p>  <p>34 PLACE STRAIN REL. CLAMP 201224-7</p> <p>Save to List Find Similar Products</p>	<p>RJ25 CONNECTORS</p>  <p>MJ, LPF, R/A, 6P/6C, SMT, TRAY PACK 5557314-1</p> <p>Save to List Find Similar Products</p>	<p>POWER CONTACTS</p>  <p>CMNL SOK 24-18 AUBR 61314-5</p> <p>Save to List Find Similar Products</p>
--	--	---	--