



# RJ25 CONNECTORS



Active

PRODUCT DRAWING  
English

3D PDF

TE CONNECTIVITY (TE)

## MJ,LPF,R/A,6P/6C,SHLD,PNL GRD

Mini PCI

5555140-1

TE Internal Number: 5555140-1

Always EU RoHS/ELV Compliant

Port Configuration **Single**

Jack Configuration **1 x 1**

Connector Style **Jack**

Inverted Jack Face **No**

Profile **Low**

### Product Drawings

[MODULAR JACK ASSEMBLY, SHIELDED, 6POSITION, LOW PROFILE, RIGHT ANGLE, PANEL GROUND WITH PANEL STOPS](#)

PDF  
English

### CAD Files

[3D PDF](#)

PDF  
3D

[Customer View Model](#)

2D\_DXF.ZIP  
English

[Customer View Model](#)

3D\_IGS.ZIP  
English

[Customer View Model](#)

3D\_STP.ZIP  
English

### Catalog Pages/Data Sheets

[82066 - Modular Jacks And MRJ21 Product Catalog - Single Port Modular Jacks Section](#)

PDF  
English

[1-1773464-9\\_MODULAR\\_JACKS\\_SINGLE\\_PORT\\_PCB\\_MOUNT](#)

PDF  
English

### Product Specifications

Product Specification

[Modular Plugs, Thru-Hole And Surface Mount Jacks, Data And Telephone, PCB Mounted](#)

PDF  
English

Application Specification

[Modular Jacks](#)

PDF  
English

### Product Environmental Compliance

TE Material Declaration

[MD\\_5555140-1\\_0623201456\\_dmtec](#)

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features	Connector Style	<b>Jack</b>
	Profile	<b>Low</b>
	PCB Mounting Orientation	<b>Side Entry (Right Angle)</b>
	Shielded	<b>Yes</b>
	Panel Stops	<b>With</b>
	Performance Category	<b>Cat 3</b>
	Latch Style	<b>Standard</b>
	Jack Type	<b>RJ25</b>
	Product Type	<b>Connector</b>
	Grounding Options	<b>PCB Ground, Panel Ground</b>
	Applies To	<b>Panel</b>
	LED	<b>Without</b>
	Connector Type	<b>Connector Assembly</b>
Configuration Features	Port Configuration	<b>Single</b>
	Jack Configuration	<b>1 x 1</b>
	Preloaded	<b>Yes</b>
	Keyed	<b>No</b>
	Number of Positions	<b>6</b>
	Number of PCB Ground Tabs	<b>2</b>
Body Features	Inverted Jack Face	<b>No</b>
	Shield Material	<b>Copper Alloy</b>
	PCB Ground Tab Location	<b>3.05 mm [ .12 in ]</b>
	Shield Plating Material	<b>Tin</b>
	Color	<b>Black</b>
Contact Features	Contact Base Material	<b>Phosphor Bronze</b>
	Solder Tail Contact Plating Material	<b>Tin over Nickel</b>
	Contact Mating Area Plating Material	<b>Gold</b>
	Contact Mating Area Plating Thickness (µin)	<b>50</b>
	Number of Contacts Loaded	<b>4</b>

Termination Features	Termination Method to PC Board	<b>Solder</b>
Mechanical Attachment	PCB Mounting Style	<b>Through Hole</b>
	Panel Mount Retention	<b>With</b>
	Flanged	<b>No</b>
Housing Features	Housing Color	<b>Black</b>
	Housing Material	<b>PBT</b>
Dimensions	PCB Thickness (Recommended)	<b>1.57 mm [ .062 in ]</b>
	Height	<b>12.7 mm [ .5 in ]</b>
	PCB Tail Length	<b>3.8 mm [ .15 in ]</b>
Industry Standards	UL Flammability Rating	<b>UL 94V-0</b>
Packaging Features	Packaging Method	<b>Package, Tray/Box</b>
	Packaging Quantity	<b>152</b>
Product Compliance	<p><a href="#">Statement of Compliance PDF</a></p> <p><a href="#">VIEW ALL PRODUCT COMPLIANCE</a></p>	

## CUSTOMERS ALSO BOUGHT

<p>MULTIPLE CONFIGURATION PCB HEADERS &amp; RECEPTACLES</p>	<p>MULTIPLE CONFIGURATION PCB HEADERS &amp; RECEPTACLES</p>	<p>DIP &amp; SIP SWITCHES</p>	<p>RECTANGULAR POWER CONNECTORS</p>
<p>10 MODII HDR DRST SFMNT B/A 146130-4</p>	<p>16 MODII HDR DRST SFMNT B/A LF 5-146130-7</p>	<p>DIP SW 3POSN AU 3-5435640-0</p>	<p>3.96 EP HDR ASSY 10P(NATURAL) 1-1123723-0</p>
<p> Save to List  Find Similar Products</p>	<p> Save to List  Find Similar Products</p>	<p> Save to List  Find Similar Products</p>	<p> Save to List  Find Similar Products</p>