

RJ45 CONNECTORS



✓ Activ

<u>±</u>

PRODUCT DRAWING



3D PDF

TE CONNECTIVITY (TE)

MJ,LPF,R/A,8P,TRAY

Mini PC

5555164-1

TE Internal Number: 5555164-1 Alias ID: 2-42938-4632

Always EU RoHS/ELV Compliant

Port Configuration Single

Shielded **No**

Jack Configuration 1 x 1

Connector Style **Jack**

Inverted Jack Face No

Product Drawings MODULAR JACK ASSEMBLY, 8 POSITION, LOW PROFILE, RIGHT ANGLE,

WITHOUT PANEL STOPS

PDF **English**

CAD Files 3D PDF

PDF **3D**

Customer View Model

3D_IGS.ZIP **English**

Customer View Model

2D_DXF.ZIP **English**

Customer View Model

3D_STP.ZIP **English**

Catalog Pages/Data Sheets 82066 - Modular Jacks And MRJ21 Product Catalog - Single Port Modular Jacks

Section PDF English

1-1773464-9_MODULAR_JACKS_SINGLE_PORT_PCB_MOUNT

PDF **English**

Product Specifications

Product Specification Modular Plugs, Thru-Hole And Surface Mount Jacks, Data And Telephone, PCB

Mounted PDF English

Application Specification Modular Jacks

PDF **English**

Product Environmental Compliance

TE Material Declaration MD 55

MD_5555164-1_05252015718_dmtec



Please review product documents or contact us for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features	Shielded	No
	Connector Style	Jack
	LED	Without
	Performance Category	Cat 3
	Profile	Low
	PCB Mounting Orientation	Side Entry (Right Angle)
	Product Type	Connector
	Latch Style	Standard
	Jack Type	RJ45
	Grounding Options	Without
	Panel Stops	Without
	D. C. C	e: 1
Configuration Features	Port Configuration	Single
	Jack Configuration	1 x 1
	Number of Positions	8
	Preloaded	Yes
	Keyed	No
Body Features	Inverted Jack Face	No
	Color	Black
Contact Features	Number of Contacts Loaded	8
	Solder Tail Contact Plating Material	Tin over Nickel
	Contact Base Material	Phosphor Bronze
	Contact Mating Area Plating Material	Gold
	Contact Mating Area Plating Thickness (µin)	50
Termination Features	Termination Method to PC Board	Solder
Mechanical Attachment	PCB Mounting Style	Through Hole
	Panel Mount Retention	With
	Flanged	No

Housing Features	Housing Material	PBT Polyester
	Housing Color	Black
Dimensions	Height	12.7 mm [.5 in]
	PCB Thickness (Recommended)	1.57 mm [.062 in]
	PCB Tail Length	3.8 mm [.15 in]
Industry Standards	UL Flammability Rating	UL 94V-0
Packaging Features	Packaging Quantity	152
	Packaging Method	Package, Tray/Box
Product Compliance	Statement of Compliance	

PDF

VIEW ALL PRODUCT COMPLIANCE