




# PCB D-SUB CONNECTORS



Active

PRODUCT DRAWING  
English

3D PDF

TE CONNECTIVITY (TE)

## RCPT ASSY,SHLD,36 POS,RTANG

CHAMP | CHAMP

5555520-2

TE Internal Number: 5555520-2

Always EU RoHS/ELV Compliant

Connector Style **Receptacle**

Centerline **2.16 mm [.085 in]**

Number of Positions **36**

Profile **Standard**

PCB Mounting Orientation **Right Angle**

### Product Drawings

RCPT ASSY, SHIELDED, 36 POSN, RIGHT ANGLE, WITH THREADED BOARDLOCK, CHAMP

PDF (TIFF AVAILABLE)  
English

RCPT ASSY, SHIELDED, 36 POSN, RIGHT ANGLE, WITH THREADED BOARDLOCK, CHAMP

PDF (TIFF AVAILABLE)  
English

### CAD Files

3D PDF

PDF  
3D

Customer View Model

2D\_DXF.ZIP  
English

Customer View Model

3D\_IGS.ZIP  
English

Customer View Model

3D\_STP.ZIP  
English

### Product Specifications

Application Specification

CHAMP Printed Circuit (PC) Board Mounted Connectors

PDF  
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features

Connector Style

**Receptacle**

Profile

**Standard**

	PCB Mounting Orientation	<b>Right Angle</b>
	Drawn Metal Shield	<b>With</b>
	Applies To	<b>Printed Circuit Board</b>
	Grounded	<b>Yes</b>
	Orientation	<b>Standard</b>
	Product Type	<b>Connector</b>
	Shielded	<b>Yes</b>
<hr/>		
Configuration Features	Number of Positions	<b>36</b>
	Preloaded	<b>Yes</b>
<hr/>		
Body Features	Plating Material	<b>Polyester</b>
	Shield Plating Material	<b>Nickel over Copper</b>
	Ground Bracket Material	<b>Carbon Steel</b>
	Color	<b>Black</b>
	Ground Bracket Plating Material	<b>Tin</b>
	Shield Plating Finish	<b>Bright</b>
	Shield Material	<b>Die Cast Metal</b>
<hr/>		
Contact Features	Solder Tail Contact Plating Material	<b>Tin</b>
	Contact Base Material	<b>Copper Alloy</b>
	Contact Mating Area Plating Thickness (µin)	<b>30</b>
	Contact Mating Area Plating Material	<b>Gold</b>
<hr/>		
Mechanical Attachment	PCB Mount Retention	<b>With</b>
	PCB Mount Retention Type	<b>Boardlocks</b>
	Mating Connector Lock	<b>With</b>
	Mating Connector Lock Type	<b>Bail Lock</b>
	Panel Mount Retention	<b>With</b>
	Screw Size	<b>14702</b>
	Boardlock Material	<b>Carbon Steel</b>
	Bail-Clip Finish	<b>Passivated</b>
	Boardlock Plating Material	<b>Tin</b>
	Mating Alignment	<b>With</b>
	Panel Attachment Style	<b>Rear Mount</b>
	Bail-Clip Material	<b>Stainless Steel</b>

---

Housing Features	Centerline	<b>2.16 mm [ .085 in ]</b>
	Housing Color	<b>Black</b>
	Housing Material	<b>Polyester GF</b>

---

Dimensions	Panel Thickness	<b>1.57 mm [ .062 in ]</b>
	PCB Thickness (Recommended)	<b>1.57 mm [ .062 in ]</b>

---

Industry Standards	UL Flammability Rating	<b>UL 94V-0</b>
--------------------	------------------------	-----------------

---

Packaging Features	Packaging Method	<b>Tray</b>
	Packaging Quantity	<b>40</b>

---

Other	Comb Material	<b>Polyester</b>
-------	---------------	------------------

---

Product Compliance [Statement of Compliance](#)  
PDF

[VIEW ALL PRODUCT COMPLIANCE](#)