



RJ22 CONNECTORS



✓ Active

↓ **PRODUCT DRAWING**
English

↓ **3D PDF**

TE CONNECTIVITY (TE)

MJ,TE,4P,W/O PNL STOPS

TE , TE-MA

5558872-1

TE Internal Number: 5558872-1

Alias ID: A08646-000, AMP-0-5558872-1

Always EU RoHS/ELV Compliant

Port Configuration **Single**

Jack Configuration **1 x 1**

Connector Style **Jack**

Inverted Jack Face **No**

Profile **Standard**

Product Drawings

MODULAR JACK ASSEMBLY, TOP ENTRY, 4 POSITION, WITHOUT PANEL STOPS

PDF **(TIFF AVAILABLE)**
English

MODULAR JACK ASSEMBLY, TOP ENTRY, 4 POSITION, WITHOUT PANEL STOPS

PDF **(TIFF AVAILABLE)**
English

CAD Files

3D PDF

PDF
English

Customer View Model

2D_DXF.ZIP
English

Customer View Model

3D_IGS.ZIP
English

Customer View Model

3D_STP.ZIP
English

Catalog Pages/Data Sheets

1-1773464-9_MODULAR JACKS_SINGLE_PORT_PCB_MOUNT

PDF
English

Product Specifications

Product Specification

Modular Plugs, Thru-Hole And Surface Mount Jacks, Data And Telephone, PCB Mounted

PDF
English

Application Specification

Modular Jacks

PDF
English

Product Type Features	Connector Style	Jack
	Profile	Standard
	PCB Mounting Orientation	Top Entry (Vertical)
	Shielded	No
	Panel Stops	Without
	Product Type	Connector

Configuration Features	Port Configuration	Single
	Jack Configuration	1 x 1
	Keyed	No

Body Features	Inverted Jack Face	No
	Color	Black

Contact Features	Solder Tail Contact Plating Material	Tin over Nickel
	Contact Mating Area Plating Thickness (µm)	1.27
	Contact Base Material	Phosphor Bronze
	Number of Contacts Loaded	4
	Contact Mating Area Plating Material	Gold

Mechanical Attachment	PCB Mounting Style	Through Hole
	Panel Mount Retention	With
	Flanged	No

Housing Features	Housing Material	PBT Polyester
------------------	------------------	----------------------













Dimensions	PCB Thickness (Recommended)	1.57 mm [.062 in]
	Height	16.5 mm [.65 in]

Industry Standards	UL Flammability Rating	UL 94V-0
--------------------	------------------------	-----------------

Packaging Features	Packaging Quantity	3328
	Packaging Method	Package, Tray/Box

Product Compliance [Statement of Compliance](#)
PDF

CUSTOMERS ALSO BOUGHT

SURFACE MOUNT RESISTORS	SURFACE MOUNT RESISTORS	SURFACE MOUNT RESISTORS	TACTILE SWITCHES
			
<p>CRG0402 1% 1K8 CRG0402F1K8</p>	<p>CPF 0402 357R 0.1% 25PPM 1K RL CPF0402B357RE1</p>	<p>CRG0402 1% 1K5 CRG0402F1K5</p>	<p>FSM4JAH=6MM TACT SWITCH, HIGH TEMP 1825910-7</p>
<p> Save to List  Find Similar Products</p>	<p> Save to List  Find Similar Products</p>	<p> Save to List  Find Similar Products</p>	<p> Save to List  Find Similar Products</p>