

## **PCB D-SUB CONNECTORS**





✓ Active



PRODUCT DRAWING



3D PDF

TE CONNECTIVITY (TE)

HD-20 PLUG 9P VERT FFSCRLK

AMPLIMITE | Standard

5745071-2

TE Internal Number: 5745071-2

Always EU RoHS/ELV Compliant

Connector Style Plug

Centerline (in) .109

Number of Positions 9

Number of Rows 2

Shell Size 1

**Product Drawings** 

PLUG ASSEMBLY, SIZE 1, 9 POSN, VERTICAL, AMPLIMITE HD-20

PDF **English** 

CAD Files

Customer View Model

2D\_DXF.ZIP

Customer View Model

3D\_IGS.ZIP English

Customer View Model

3D\_STP.ZIP English

3D PDF

PDF **English** 

Catalog Pages/Data Sheets

AMPLIMITE Subminiature D Connectors - Straight Posted Connectors

PDF **English** 

Please review product documents or contact us for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

**Product Type Features** 

Connector Style

Plug

Shell Size

1

Profile

Standard

PCB Mounting Orientation

Vertical

Grounding Straps

Without

Shall Type


All Disetic


	эпен туре	All Flastic
	Grounding Indents	Without
	Applies To	Printed Circuit Board
	Sealed	No
	Grounded	No
	Product Type	Connector
	Shielded	No
0.5.4.5.4	N. J. (8. W.	•
Configuration Features	Number of Positions	9
	Number of Rows	2
	Preloaded	Yes
Body Features	Plastic	Yes
	Female Screwlock Material	Brass
	Female Screwlock Plating Material	Nickel over Copper Flash
	Color Code	None
	Post Size	.66 mm [ .026 in ]
Contact Features	Contact Shape	Round
	Solder Tail Contact Plating Material	Tin over Nickel
	Contact Base Material	Brass
	Contact Mating Area Plating Thickness (μin)	30
	Contact Mating Area Plating Material	Gold
Termination Features	Termination Post Length	3.18 mm [.125 in]
	Grounding Clips	Without
Mechanical Attachment	PCB Mounting Style	Through Hole
	PCB Mount Retention	With
	PCB Mount Retention Type	Mounting Holes
	Mating Connector Lock	With
	Mating Connector Lock Type	Female Screwlocks, Fixed
	Panel Mount Retention	Without
	Mounting Hole Diameter	3.05 mm [ .12 in ]
Housing Features	Centerline (in)	.109
Todaling reduces		Black
	Housing Color	DIACK

	Housing Material	Polyester
Dimensions	PCB Thickness (Recommended)	1.57 – 2.36 mm [ .062 – .093 in ]
Industry Standards	UL Flammability Rating	UL 94V-0
Packaging Features	Packaging Method  Packaging Quantity	Tube
Other	Comment	Plugs are preloaded with size 20 DF posted pin contacts
Product Compliance	Statement of Compliance PDF	

## VIEW ALL PRODUCT COMPLIANCE

### **CUSTOMERS ALSO BOUGHT**





Connector Style **Receptacle** 

Number of Positions 9

09 HDE AP RECEPT,

LEAD FREE - 745201-7





TE INTERNAL NUMBER: 745201-7

✓ Active

Number of Rows 2

Preloaded **Yes** 

Contact Size 20

RELATIONSHIP

Mating Products
Used to identify Mating Parts

See All Mating Products



PRODUCT - MATING PRODUCTS

Connectors - IDC D-Sub Connectors
AMPLIMITE I HDF for Flat Ribbon Cable
09 POS HDF RCPT, AP,

LEAD FREE - 1658609-4
TE INTERNAL NUMBER: 1658609-4

✓ Active

#### Always EU RoHS/ELV Compliant

Connector Style **Receptacle** 

Number of Positions 9

Number of Rows 2

Preloaded **Yes** 

Contact Size 20

RELATIONSHIP

# Mating Products

Used to identify Mating Parts

See All Mating Products



PRODUCT - MATING PRODUCTS

Connectors - IDC D-Sub Connectors
AMPLIMITE I HDF for Flat Ribbon Cable
09 POS HDF RCPT, AP,
LEAD FREE - 1658614-4

TE INTERNAL NUMBER: 1658614-4

✓ Active

#### Always EU RoHS/ELV Compliant

Connector Style **Receptacle** 

Number of Positions 9

Number of Rows 2

Preloaded **Yes** 

Contact Size **20** 

