

PCB D-SUB CONNECTORS







PRODUCT DRAWING



3D PDF

TE CONNECTIVITY (TE)

09 MSFL RCPT RA 318 (SL,FM,BL)

AMPLIMITE | SL , Standard

5747844-6

TE Internal Number: 5747844-6

Alias ID: 1033323, 1352649, 1363572, 1367706

Always EU RoHS/ELV Compliant

Connector Style Receptacle

Centerline (in) .108

Number of Positions 9

Number of Rows 2

Shell Size 1

Product Drawings

RECEPTACLE ASSEMBLY, SIZE 1, RIGHT ANGLE, .318 SERIES, FRONT METAL

SHELL, .026 DIA POSTS, BOARDLOCKS, AMPLIMITE HD-20

PDF English

CAD Files

Customer View Model

2D_DXF.ZIP English

Customer View Model

3D_IGS.ZIP English

Customer View Model

3D_STP.ZIP English

3D PDF

PDF **English**

Catalog Pages/Data Sheets

AMPLIMITE Subminiature D Connectors - Right-Angle Posted Connectors

PDF **English**

Product Environmental Compliance

TE Material Declaration

MD_5747844-6_121920131123_dmtec

PDF **English**

Please review product documents or contact us for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features

Connector Style

Receptacle

Shell Size

1


	Profile	Standard	
	PCB Mounting Orientation		
	Grounding Straps	Right Angle With	
	Shell Type	Front Metal Shell	
	Footprint	8.08 mm [.318 in]	
	Grounding Indents	Without	
	Applies To	Printed Circuit Board	
	Sealed	No	
	Grounded	No	
	Product Type	Connector	
Configuration Features	Number of Positions	9	
	Number of Rows	2	
	Preloaded	Yes	
Body Features	Plastic	No	
	Female Screwlock Material	Zinc	
	Female Screwlock Plating Material	Clear Chromate	
	Color Code	None	
	Eyelet Plating Material	Tin	
	Shell Plating Material	Tin	
	Insert Material	Zinc	
	Shell Material	Steel	
	Eyelet Material	Brass	
	Post Size	.66 mm [.026 in]	
Contact Features	Contact Shape	Round	
	Solder Tail Contact Plating Material	Tin	
	Contact Base Material	Phosphor Bronze	
	Contact Mating Area Plating Thickness (µin)	30	
		Gold	
	Contact Mating Area Plating Material	Gold	
Termination Features	Termination Post Length	3.18 mm [.125 in]	
Totaliadon i edidico		Without	
	Grounding Clips	without	
Mechanical Attachment	PCB Mounting Style	Through Hole	
TO STATISTIC TO STATE OF THE ST	DCD Marint Datastics	Mr.a.L	

	PCB IVIOUNT RETENTION	witn	
	PCB Mount Retention Type	Boardlocks	
	Mating Connector Lock	With	
	Mating Connector Lock Type Female Screwlocks, Fixed		
	Panel Mount Retention	Without	
	Mating Retention Type	Screw	
	Boardlock Material	Copper Alloy	
	Mating Retention	With	
	PCB Mount Alignment	With	
	Mounting Hole Diameter	3.18 mm [.125 in]	
	Boardlock Plating Material	Tin	
Housing Features	Centerline (in)	.108	
	Housing Color	Black	
	Housing Material	Thermoplastic	
Dimensions	PCB Thickness (Recommended)	1.58 mm [.062 in]	
Industry Standards	UL Flammability Rating	UL 94V-0	
Packaging Features	Packaging Method	Tray	
	Packaging Quantity	130	
Other	Comment	All receptacles are preloaded with size 20 DF posted socket contacts	
Product Compliance	Statement of Compliance		

VIEW ALL PRODUCT COMPLIANCE

CUSTOMERS ALSO BOUGHT





RELATIONSHIP



Connectors - PCB D-Sub Connectors AMPLIMITE | Standard

HD-20 PLUG RA .318 FMS BD-LK 4 - 5747840-4 TE INTERNAL NUMBER: 5747840-4

✓ Active

Always EU RoHS/ELV Compliant

Connector Style Plug Centerline 2.74 mm

Number of Positions 9

Number of Rows 2

Shell Size 1