

PCB D-SUB CONNECTORS





✓ Active



PRODUCT DRAWING



3D PDF

TE CONNECTIVITY (TE)

15 MSFL RCPT RA 318 (IN,FM,BL)

AMPLIMITE | Standard

5747845-3

TE Internal Number: 5747845-3

Always EU RoHS/ELV Compliant

Connector Style Receptacle

Centerline (in) .108

Number of Positions 15

Number of Rows 2

Shell Size 2

Product Drawings

RECEPTACLE ASSEMBLY, SIZE 2, 15 POSITION, RIGHT ANGLE, FRONT METAL SHELL, .318 SERIES, .026 DIA POSTS, BOARDLOCKS, AMPLIMITE HD-20

PDF **English**

CAD Files

Customer View Model

2D_DXF.ZIP **English**

Customer View Model

3D_IGS.ZIP **English**

Customer View Model

3D_STP.ZIP **English**

3D PDF

PDF **English**

Catalog Pages/Data Sheets

AMPLIMITE Subminiature D Connectors - Right-Angle Posted Connectors

PDF **English**

Product Environmental Compliance

TE Material Declaration

MD_5747845-3_12072011131

PDF English

Please review product documents or contact us for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features

Connector Style

Receptacle

Shell Size

2

	Profile	Standard
	PCB Mounting Orientation	Right Angle
	Grounding Straps	With
	Shell Type	Front Metal Shell
	Footprint	8.08 mm [.318 in]
	Grounding Indents	Without
	Applies To	Printed Circuit Board
	Sealed	No
	Grounded	No
	Product Type	Connector
Configuration Features	Number of Positions	15
	Number of Rows	2
	Preloaded	Yes
Body Features	Plastic	No
	Color Code	None
	Eyelet Plating Material	Tin
	Shell Plating Material	Tin
	Insert Material	Zinc
	Shell Material	Carbon Steel
	Eyelet Material	Brass
	Post Size	.66 mm [.026 in]
Contact Features	Contact Shape	Round
	Solder Tail Contact Plating Material	Tin
	Contact Base Material	Phosphor Bronze
	Contact Mating Area Plating Material	Gold Flash
Termination Features	Termination Post Length	3.18 mm [.125 in]
	Grounding Clips	Without
Mechanical Attachment	PCB Mounting Style	Through Hole
	PCB Mount Retention	With
	PCB Mount Retention Type	Boardlocks
	Mating Connector Lock	With
	Matina Connector Look Time	Throaded Income A AO LINIC

Inreaded Insert, 4-40 UNC iviating Connector Lock Type Panel Mount Retention Without Mating Retention Type **Threaded Inserts** Boardlock Material Copper Alloy Mating Retention With PCB Mount Alignment With Mounting Hole Diameter 3.18 mm [.125 in] Boardlock Plating Material Tin over Nickel Threaded Insert Material Zinc Threaded Insert Plating Material **Clear Chromate** Housing Features Centerline (in) .108 Housing Color Black Housing Material Thermoplastic PCB Thickness (Recommended) Dimensions 1.57 mm [.062 in] Industry Standards **UL Flammability Rating** UL 94V-0 Packaging Features Packaging Method Tray Packaging Quantity 104 Other Comment All receptacles are preloaded with size 20 DF posted socket contacts **Product Compliance** Statement of Compliance PDF VIEW ALL PRODUCT COMPLIANCE



RELATIONSHIP

Mating Products
Used to identify Mating Parts

See All Mating Products



Connectors - PCB D-Sub Connectors AMPLIMITE | Standard

15 MSFL PLUG RA 318 (IN, FM, BL) - 5747841-3 TE INTERNAL NUMBER: 5747841-3

Always EU RoHS/ELV Compliant

Connector Style Plug

Centerline 2.74 mm

Number of Positions 15

Number of Rows 2

Shell Size 2

RELATIONSHIP

Mating Products

Used to identify Mating Parts

See All Mating Products



PRODUCT - MATING PRODUCTS

Connectors - PCB D-Sub Connectors AMPLIMITE | Standard

15 MSFL PLUG RA 318 (IN, FM, BL) - 5747841-4 TE INTERNAL NUMBER: 5747841-4

✓ Active

Always EU RoHS/ELV Compliant

Connector Style Plug

Centerline 2.74 mm

Number of Positions 15

Number of Rows 2

Shell Size 2

RELATIONSHIP

Mating Products

Used to identify Mating Parts

See All Mating Products



PRODUCT - MATING PRODUCTS

Connectors - IDC D-Sub Connectors AMPLIMITE | HDE (IDC) Insulation

KIT, PLUG, 15P, HDE, SHLD ENCLSRE - 1-747946-6

TE INTERNAL NUMBER: 1-747946-6

✓ Active

Always EU RoHS/ELV Compliant

Connector Style Plug

Shielded Yes

Number of Positions 15

Number of Rows 2

Preloaded Yes

