

PCB D-SUB CONNECTORS







PRODUCT DRAWING



3D PDF

TE CONNECTIVITY (TE)

25 MSFL RCPT RA 318 (SL,FM,BL)

AMPLIMITE | SL , Standard

5747846-6

TE Internal Number: 5747846-6

Always EU RoHS/ELV Compliant

Connector Style Receptacle

Centerline (in) .109

Number of Positions 25

Number of Rows 2

Shell Size 3

Product Drawings

RECEPTACLE ASSEMBLY, SIZE 3, 25 POSITION, RIGHT ANGLE, FRONT METAL

SHELL, .318 SERIES, .026 DIA POSTS, BOARDLOCKS, AMPLIMITE HD-20

PDF English

CAD Files

Customer View Model

2D_DXF.ZIP English

Customer View Model

3D_IGS.ZIP English

Customer View Model

3D_STP.ZIP English

3D PDF

PDF **English**

Catalog Pages/Data Sheets

AMPLIMITE Subminiature D Connectors - Right-Angle Posted Connectors

PDF **English**

Product Specifications

Product Specification AMPLIMITE HD-20 PCB Mounted Connector

PDF **English**

Application Specification AMPLIMITE Right-Angle Front Metal Shell Connectors

> PDF English

Product Environmental Compliance

TE Material Declaration

MD_5747846-6_0308201686_dmtec

English

Please review product documents or contact us for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.


Product Type Features	Connector Style	Receptacle	
	Shell Size	3	
	Profile	Standard	
	PCB Mounting Orientation	Right Angle	
	Grounding Straps	With	
	Shell Type	Front Metal Shell	
	Footprint	8.08 mm [.318 in]	
	Grounding Indents	Without	
	Applies To	Printed Circuit Board	
	Sealed	No	
	Grounded	No	
	Product Type	Connector	
Configuration Features	Number of Positions	25	
	Number of Rows	2	
	Preloaded	Yes	
Body Features	Plastic	No	
	Female Screwlock Material	Zinc	
	Female Screwlock Plating Material	Clear Chromate	
	Color Code	None	
	Eyelet Plating Material	Tin	
	Shell Plating Material	Tin	
	Insert Material	Zinc	
	Shell Material	Carbon Steel	
	Eyelet Material	Brass	
	Post Size	.66 mm [.026 in]	
Contact Features	Contact Shape	Round	
	Solder Tail Contact Plating Material	Tin	
	Contact Base Material	Phosphor Bronze	
	Contact Mating Area Plating Thickness (µin)	30	
	Contact Mating Area Plating Material	Gold	

Termination Features	Termination Post Length 3.18 mm [.125 in]		
	Grounding Clips	Without	
Mechanical Attachment	PCB Mounting Style	Through Hole	
	PCB Mount Retention	With	
	PCB Mount Retention Type	Boardlocks	
	Mating Connector Lock	With	
	Mating Connector Lock Type	Female Screwlocks, Fixed	
	Panel Mount Retention	Without	
	Mating Retention Type	Screw	
	Boardlock Material	Brass	
	Mating Retention	With	
	PCB Mount Alignment	With	
	Mounting Hole Diameter	3.18 mm [.125 in]	
	Boardlock Plating Material	Tin over Nickel	
Housing Features	Centerline (in)	.109	
	Housing Color	Black	
	Housing Material	Thermoplastic	
Dimensions	PCB Thickness (Recommended)	1.57 mm [.062 in]	
Industry Standards	UL Flammability Rating	UL 94V-0	
Packaging Features	Packaging Method	Тгау	
	Packaging Quantity	65	
Other	Comment All receptacles are preloaded with size 20 DF posted socket contacts		
Double Constitute			
Product Compliance	Statement of Compliance PDF		

VIEW ALL PRODUCT COMPLIANCE

CUSTOMERS ALSO BOUGHT

PCB D-SUB CONNECTORS	THROUGH-HOLE RESISTORS	RJ25 CONNECTORS	SURFACE MOUNT RESISTORS
1 05 5 005 0011112010110	11111000111102211201010110	11020 0011112010110	





KIT, PLUG, 25P, HDE, SHLD ENCLSRE - 1-747948-6 TE INTERNAL NUMBER: 1-747948-6

✓ Active

Connector Style **Plug**

Shielded **Yes**

Number of Positions 25

Number of Rows 2

Preloaded **Yes**