

#### **PCB D-SUB CONNECTORS**





✓ Active



PRODUCT DRAWING



3D PDF

TE CONNECTIVITY (TE)
25 RCPT SP/FMS BRDLK

AMPLIMITE | FSM , SP

5748612-1

TE Internal Number: 5748612-1

Always EU RoHS/ELV Compliant

Connector Style Receptacle

Centerline (in) .108

Number of Positions 25

Number of Rows 2

Shell Size 3

Product Drawings RECEPT ASSY, SIZE 3, 25 POSN, VERT, FRT METAL SHELL, RETENTION

SCREWLOCKS, AMPLIMITE HD-20

PDF (TIFF AVAILABLE)

English

RECEPT ASSY, SIZE 3, 25 POSN, VERT, FRT METAL SHELL, RETENTION

SCREWLOCKS, AMPLIMITE HD-20

PDF (TIFF AVAILABLE)

English

CAD Files Customer View Model

2D\_DXF.ZIP **English** 

**Customer View Model** 

3D\_IGS.ZIP **English** 

**Customer View Model** 

3D\_STP.ZIP English

3D PDF PDF English

Catalog Pages/Data Sheets AMPLIMITE Subminiature D Connectors - Straight Posted Connectors

PDF **English** 

**Product Specifications** 

Product Specification AMPLIMITE HD-20 PCB Mounted Connector

PDF **English** 

Application Specification AMPLIMITE HD-20 Straight Solder Contact Tine, Front Metal Shell, PC Board And

Panel Mount Connectors

PDF **English** 

Qualification Test Report Connector, AMPLIMITE HD-20, Printed Circuit Board Mounted

PDF **English** 

### MD\_5748612-1\_061620141041\_dmtec

PDF English

Please review product documents or contact us for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features	Connector Style	Receptacle
	Shell Size	3
	Profile	Standard
	PCB Mounting Orientation	Vertical
	Grounding Straps	Without
	Shell Type	Front Metal Shell
	Grounding Indents	Without
	Applies To	Printed Circuit Board
	Sealed	No
	Product Type	Connector
Configuration Features	Number of Positions	25
	Number of Rows	2
	Preloaded	Yes
Body Features	Plastic	No
	Female Screwlock Material	Zinc
	Color Code	None
	Shell Plating Material	Tin
	Shell Material	Carbon Steel
	Post Size	.66 mm [ .026 in ]
Contact Features	Contact Shape	Round
	Solder Tail Contact Plating Material	Tin over Nickel
	Contact Base Material	Phosphor Bronze
	Contact Mating Area Plating Thickness (µin)	30
	Contact Mating Area Plating Material	Gold
	Contact Mating Alea Hating Material	Colu
Termination Features	Termination Post Length	3.18 mm [ .125 in ]
	Grounding Clips	Without

Mechanical Attachment PCB Mounting Style **Through Hole** With PCB Mount Retention 4-40 Retention Screwlocks PCB Mount Retention Type Mating Connector Lock Without Panel Mount Retention Without Mounting Hole Diameter 3.07 mm [ .121 in ] .108 Housing Features Centerline (in) Housing Color Black Housing Material Polyester Dimensions PCB Thickness (Recommended) 1.57 mm [ .062 in ] **UL Flammability Rating** UL 94V-0 Industry Standards **Packaging Features** Packaging Method Tube 10 Packaging Quantity Other Comment All receptacles are preloaded with size 20 **DF** posted socket contacts **Product Compliance** Statement of Compliance

VIEW ALL PRODUCT COMPLIANCE



RELATIONSHIP

Mating Products

Used to identify Mating Parts

See All Mating Products



PRODUCT - MATING PRODUCTS

Connectors - IDC D-Sub Connectors AMPLIMITE | HDE (IDC) Insulation

25 HDE MS PLUG, 22-26, LEAD FREE - 1-745496-7 TE INTERNAL NUMBER: 1-745496-7 ALIAS ID: AMP-1-0745496-7, C29226-000 Always EU RoHS/ELV Compliant

Connector Style **Plug** 

Centerline 1.38 mm

Number of Positions 25

✓ Active

Number of Rows 2

Preloaded Yes

RELATIONSHIP

## Mating Products Used to identify Mating Parts

See All Mating Products



PRODUCT - MATING PRODUCTS

Connectors - IDC D-Sub Connectors
AMPLIMITE I HDF for Flat Ribbon Cable
25 POS HDF PLUG, MS,
LEAD FREE - 1658608-2
TE INTERNAL NUMBER: 1658608-2



#### Always EU RoHS/ELV Compliant

Connector Style Plug

Number of Positions 25

Number of Rows 2

Preloaded **Yes** 

Contact Size 20

RELATIONSHIP

# Mating Products Used to identify Mating Parts

PRODUCT - MATING PRODUCTS

Connectors - IDC D-Sub Connectors AMPLIMITE | HDE (IDC) Insulation

PLUG ASSY, 25P, HDE, MS - 1-745496-9
TE INTERNAL NUMBER: 1-745496-9

✓ Active

Always EU RoHS/ELV Compliant

Connector Style **Plug** 

Centerline 1.38 mm

Number of Positions 25

Number of Rows 2

Preloaded **Yes** 





See All Mating Products