

# PCB D-SUB CONNECTORS

У 🖬 f 🔻





## TE CONNECTIVITY (TE) 09 RCPT SP/FMS (RET SL) AMPLIMITE | SP , Standard

5750678-1 TE Internal Number: 5750678-1

#### Always EU RoHS/ELV Compliant

Connector Style **Receptacle** Centerline (mm) **2.74** 

Number of Positions 9

Number of Rows 2

Shell Size 1

Product Drawings	RECEPTACLE ASSEMBLY, SIZE 1, 9 POSN, VERTICAL, FRONT METAL SHELL, AMPLIMITE HD-20 PDF English		
CAD Files	Customer View Model 2D_DXF.ZIP English		
	Customer View Model 3D_IGS.ZIP English		
	Customer View Model 3D_STP.ZIP English		
	3D PDF PDF English		
Catalog Pages/Data Sheets	AMPLIMITE Subminiature D Connectors - Straight Posted Connectors PDF English		
Product Specifications			
Product Specification	AMPLIMITE HD-20 PCB Mounted Connector PDF English		
Application Specification	AMPLIMITE HD-20 Straight Solder Contact Tine, Front Metal Shell, PC Board And Panel Mount Connectors PDF English		
Qualification Test Report	Connector, AMPLIMITE HD-20, Printed Circuit Board Mounted PDF English		

### Product Environmental Compliance

TE Material Declaration

MD\_5750678-1\_061620141042\_dmtec PDF English Please review product documents or **contact us** for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features	Connector Style	Receptacle
	Shell Size	1
	Profile	Standard
	PCB Mounting Orientation	Vertical
	Grounding Straps	Without
	Shell Type	Front Metal Shell
	Grounding Indents	Without
	Applies To	Printed Circuit Board
	Sealed	Νο
	Product Type	Connector
Configuration Features	Number of Positions	9
	Number of Rows	2
	Preloaded	Yes
Body Features	Plastic	Νο
	Female Screwlock Material	Zinc
	Color Code	None
	Shell Plating Material	Tin
	Shell Material	Carbon Steel
	Post Size	.66 mm [ .026 in ]
Contact Features	Contact Shape	Round
	Solder Tail Contact Plating Material	Tin over Nickel
	Contact Base Material	Phosphor Bronze
	Contact Mating Area Plating Thickness (µin)	30
	Contact Mating Area Plating Material	Gold
Termination Features	Termination Post Length	3.18 mm [ .125 in ]
	Grounding Clips	Without
Mechanical Attachment	PCB Mounting Style	Through Hole
	PCB Mount Retention	With

	- OD mount notention	
	PCB Mount Retention Type	4-40 Retention Screwlocks
	Mating Connector Lock	Without
	Panel Mount Retention	Without
	Mounting Hole Diameter	3.07 mm [ .121 in ]
Housing Features	Centerline (mm)	2.74
	Housing Color	Black
	Housing Material	РВТ
Dimensions	PCB Thickness (Recommended)	1.57 mm [ .062 in ]
Industry Standards	UL Flammability Rating	UL 94V-0
Packaging Features	Packaging Method	Tube
	Packaging Quantity	17
Other	Comment	All receptacle assemblies are preloaded with size 20 DF posted socket contacts.
Product Compliance	Statement of Compliance	
	PDF	
	VIEW ALL PRODUCT COMPLIANCE	

# CUSTOMERS ALSO BOUGHT

THROUGH-HOLE RESISTORS	RECTANGULAR POWER CONNECTORS	СХР	HARD METRIC BACKPLANE CONNECTORS	
LR1 1% 1K8 LR1F1K8	2MM FB, ASY, 008, PWR, REC, EN, 3.56 5536614-1	CXP RCPT KIT W/HEAT SINK 2149157-1	2MM HM ASY, T-B, HDR, 10R, 250, AP 5646357-1	
Save to List	Save to List	Save to List	Save to List	
•				

Relation Type	•			
RELATIONSHIP Mating Products				
Used to identify Mating Parts			See All Mating Pro	ducts
	PRODUCT - MATING PRODUCTS			~
	Connectors - IDC D-Sub Connectors AMPLIMITE I HDE (IDC) Insulation	Always EU RoHS/ELV Compli	ant	
	09 HDE PMOLD PLUG, LEAD FREE - 747515-7 TE INTERNAL NUMBER: 747515-7 ✓ Active	Connector Style <b>Plug</b>		
		Shielded Yes		
		Centerline 1.38 mm		
		Number of Positions <b>9</b>		
		Number of Rows <b>2</b>		

# RELATIONSHIP Mating Products Used to identify Mating Parts PRODUCT - MATING PRODUCTS Connectors - IDC D-Sub Connectors AMPLIMITE I HDE (IDC) Insulation 09 HDE MS PLUG, 26-30,

LEAD FREE - 1-745492-7 TE INTERNAL NUMBER: 1-745492-7

✓ Active

#### Always EU RoHS/ELV Compliant

Connector Style **Plug** Number of Positions **9** Number of Rows **2** 

Preloaded **Yes** 

Contact Size 20

#### RELATIONSHIP **Mating Products** Used to identify Mating Parts



#### PRODUCT - MATING PRODUCTS

Connectors - IDC D-Sub Connectors AMPLIMITE I HDF for Flat Ribbon Cable 09 POS HDF PLUG, MS,



✓ Active

### Always EU RoHS/ELV Compliant

Connector Style **Plug** Number of Positions **9** Number of Rows **2** Preloaded **Yes** Contact Size **20** 

#### See All Mating Products

See All Mating Products

 $\sim$