



TE CONNECTIVITY (TE) USB A R/A STAK ASSY THRU HOLE

Universal Serial Bus | A

5787745-1
TE Internal Number: 5787745-1

Always EU RoHS/ELV Compliant

Size **Standard**

Connector Style **Receptacle**

Number of Positions **8**

Number of Ports **2**

Orientation **Right Angle**

Active

PRODUCT DRAWING
English

3D PDF

Product Drawings

[RECEPTACLE ASSEMBLY, RIGHT ANGLE, STACKED, THRU-HOLE, USB](#)

PDF
English

CAD Files

[Customer View Model](#)

2D_DXF.ZIP
English

[3D PDF](#)

PDF
3D

[Customer View Model](#)

3D_IGS.ZIP
English

[Customer View Model](#)

3D_STP.ZIP
English

Product Specifications

Product Specification

[Product Specification For Usb Consortium Plug & Receptacle Lead Free Version](#)

PDF
English

Application Specification

[Universal Serial Bus \(USB\) Connectors](#)

PDF
English

Qualification Test Report

[Test Report For USB Consortium Plug & Receptacle Lead Free Version](#)

PDF
English

Product Environmental Compliance

TE Material Declaration

[MD_5787745-1_06222015737_dmtec](#)

PDF
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features	Size	Standard
	Connector Style	Receptacle
	Orientation	Right Angle
	LED	Without
	Product Type	Connector
	Applies To	Printed Circuit Board
Configuration Features	Number of Positions	8
	Number of Ports	2
	Panel Ground	With
	Panel Ground Location	Between Ports
	Panel Ground Type	Ground Finger
Body Features	Shell Plating Material	Tin
	Shell Plating Finish	Bright
Contact Features	Contact Mating Area Plating Thickness	.76 μm [29.92 μin]
	Contact Mating Area Plating Material	Gold or Gold Flash over Palladium Nickel
Termination Features	Termination Method	Solder
	Contact Termination Type	Through Hole
Mechanical Attachment	Mounting Location	Top
	Locking Feature	Without
	Locating Posts	Without
	PCB Mount Retention Type	Kinked Legs
Housing Features	Housing Material	Thermoplastic
	Housing Color	Black
Dimensions	Tail Length	2.84 mm [.112 in]
	PCB Thickness (Recommended)	1.57 mm [.062 in]
Operation/Application	Pick and Place	None
	Industrial USB Connector	No

Packaging Features

Packaging Method

Tray, Tray/Box

Packaging Quantity

88













Product Compliance

[Statement of Compliance](#)

PDF

[VIEW ALL PRODUCT COMPLIANCE](#)

CUSTOMERS ALSO BOUGHT

CRIMP QUICK DISCONNECTS	BNC CONNECTORS	HDMI CONNECTORS	WIRE-TO-BOARD HEADERS & RECEPTACLES
			
<p>.250 SRS FLAG FASTON RECEPTACLE 180429-1</p>	<p>RTANG JACK, BNC PCB 226990-1</p>	<p>ASSY HDMI RECEPTACLE SMT 2-1747981-3</p>	<p>EIS POST HDR V 3P 172487-3</p>
<p> Save to List</p> <p> Find Similar Products</p>	<p> Save to List</p> <p> Find Similar Products</p>	<p> Save to List</p> <p> Find Similar Products</p>	<p> Save to List</p> <p> Find Similar Products</p>