



QUICK DISCONNECTS



TE CONNECTIVITY (TE)

FAST REC IS 22-18 PTPBR

[FASTON](#) | [FASTON Terminals and Housings](#)

60432-1

TE Internal Number: 60432-1

Always EU RoHS/ELV Compliant

Mating Tab Width **2.62 mm [.103 in]**

Mating Tab Thickness **.51 mm [.02 in]**

Wire Insulation Diameter **2.03 – 3.05 mm [.08 – .12 in]**

Wire Size (AWG) **20 – 18**

Wire Size (mm²) **.5 – .8**

✓ Active

[↓ PRODUCT DRAWING](#)
English

[↓ 3D PDF](#)

Product Drawings

[RECEPTACLE, FASTON, SPECIAL](#)

PDF
English

CAD Files

[Customer View Model](#)

2D_DXF.ZIP
English

[3D PDF](#)

PDF
3D

[Customer View Model](#)

3D_IGS.ZIP
English

[Customer View Model](#)

3D_STP.ZIP
English

Catalog Pages/Data Sheets

[82004 FASTON Terminals \(Insulated And Uninsulated\) Catalog - FASTON Receptacles Section](#)

PDF
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features

Insertion Force	Normal
FASTON	Yes
Wire/Cable Composition	Stranded
Insulated	No
Insulated Wire Support	No

	Support Style	Insulation Support
	Applies To	Wire/Cable
Configuration Features	Paired	No
	Terminal Angle	Straight
Body Features	Plating Material	Brass, Pre-Tin
Contact Features	Terminal Orientation	Straight
	Contact Plating Material	Pre-Tin
Termination Features	Crimp Type	F-Crimp
Mechanical Attachment	Mating Retention Type	Dimple
Dimensions	Mating Tab Width	2.62 mm [.103 in]
	Mating Tab Thickness	.51 mm [.02 in]
	Wire Insulation Diameter	2.03 – 3.05 mm [.08 – .12 in]
	Wire Size (AWG)	20 – 18
	Wire Size (mm ²)	.5 – .8
	Material Thickness	.25 mm [.01 in]
	Overall Length	13.71 mm [.54 in]
Packaging Features	Packaging Method	Reel
	Packaging Quantity	10000
Other	Line	Budget
Product Compliance	Statement of Compliance PDF VIEW ALL PRODUCT COMPLIANCE	