



# PCB TERMINALS



## TE CONNECTIVITY (TE) 110 FAST TAB PCB 020TPCUBR FASTON | 110

61134-3  
TE Internal Number: 61134-3

Always EU RoHS/ELV Compliant

Terminal Style **Tab**

PCB Thickness (Recommended) **.81 – 2.36 mm [ .032 – .093 in ]**

Mating Tab Width **2.79 mm [ .11 in ]**

Mating Tab Thickness **.51 mm [ .02 in ]**

PCB Hole Diameter **1.45 mm [ .057 in ]**

Active

PRODUCT DRAWING  
English

3D PDF

### Product Drawings

[TAB, FASTON, P.C.BOARD, .110 SERIES](#)

PDF  
English

### CAD Files

[3D PDF](#)

PDF  
3D

[Customer View Model](#)

2D\_DXF.ZIP  
English

[Customer View Model](#)

3D\_IGS.ZIP  
English

[Customer View Model](#)

3D\_STP.ZIP  
English

### Catalog Pages/Data Sheets

[FASTON PCB Tabs And Receptacles](#)

PDF  
English

[PRINTED CIRCUIT BOARD TERMINALS AND DISCONNECTS](#)

PDF  
English

### Product Specifications

Application Specification

[FASTON 110, 187, 205, 250, And 312 Series Tab Contacts For Printed Circuit \(PC\) Board Applications](#)

PDF  
English

Qualification Test Report

[110 Series Positive Lock EX-III Conn.](#)

PDF  
English


[110 Series Positive Lock EX-III Conn.](#)

TIF  
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

|                        |  |   |
|------------------------|--|---|
| Product Type Features  | Applies To   | <b>Printed Circuit Board</b>            |
|                        | Insulated Wire Support   | <b>Yes</b>                              |
| Configuration Features | Stud Hole  | <b>No</b>                               |
|                        | Terminal Angle   | <b>Straight</b>                         |
| Body Features          | Plating Material   | <b>Tin</b>                              |
| Contact Features       | Terminal Style   | <b>Tab</b>                              |
|                        | Contact Plating Material   | <b>Tin</b>                              |
| Dimensions             | PCB Thickness (Recommended)  | <b>.81 – 2.36 mm [ .032 – .093 in ]</b> |
|                        | Mating Tab Width   | <b>2.79 mm [ .11 in ]</b>               |
|                        | Mating Tab Thickness   | <b>.51 mm [ .02 in ]</b>                |
|                        | PCB Hole Diameter  | <b>1.45 mm [ .057 in ]</b>              |
| Industry Standards     | UL Rating  | <b>Recognized</b>                       |
|                        | CSA Certified  | <b>Yes</b>                              |
| Packaging Features     | Packaging Method   | <b>Bag</b>                              |
|                        | Packaging Quantity   | <b>1000</b>                             |
| Product Compliance     | <a href="#">Statement of Compliance PDF</a><br><a href="#">VIEW ALL PRODUCT COMPLIANCE</a> |   |

## CUSTOMERS ALSO BOUGHT

|  |   |  |  |
|--|---|--|--|
| <p><b>SURFACE MOUNT RESISTORS</b></p>  <p><b>RN 0805 14K7 0.1% 10PPM 1KRL<br/>RN73C2A14K7BTDf</b></p> | <p><b>RECTANGULAR POWER CONNECTORS</b></p>  <p><b>20P MINI UMNL R/A HDR ASSY LF<br/>1-794106-1</b></p> | <p><b>WIRE-TO-BOARD CONNECTOR CONTACTS</b></p>  <p><b>EIS CONN PIN CONTACT<br/>170377-2</b></p> | <p><b>STANDARD RECTANGULAR CONNECTORS</b></p>  <p><b>DYNAMIC D3 HDR ASSY V 20P<br/>178328-5</b></p> |
|--|---|--|--|

