



## QUICK DISCONNECTS



TE CONNECTIVITY (TE)

### 110 FL FAST REC 22-18 010PTPBR

FASTON | 110

61971-1

TE Internal Number: 61971-1

Always EU RoHS/ELV Compliant

Mating Tab Width **2.79 mm [ .11 in ]**

Mating Tab Thickness **.8 mm [ .032 in ]**

Wire Insulation Diameter **1.65 – 2.54 mm [ .065 – .1 in ]**

Wire Size (AWG) **22 – 18**

Wire Size (mm²) **.3 – .8**

Active

[PRODUCT DRAWING](#)  
English

[3D PDF](#)

#### Product Drawings

[RECEPTACLE, FASTON, FLAG, .110 SERIES](#)

PDF  
English

#### CAD Files

[Customer View Model](#)

2D\_DXF.ZIP  
English

[3D PDF](#)

PDF  
3D

[Customer View Model](#)

3D\_IGS.ZIP  
English

[Customer View Model](#)

3D\_STP.ZIP  
English

#### Catalog Pages/Data Sheets

[82004 FASTON Terminals \(Insulated And Uninsulated\) Catalog - FASTON Receptacles Section](#)

PDF  
English

#### Product Specifications

Application Specification

[FASTON 110 Series Flag Receptacles With "F" Crimp Feature](#)

PDF  
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features

Insertion Force

Normal

FASTON

Yes

	Wire/Cable Composition	<b>Stranded</b>
	Insulated	<b>No</b>
	Support Style	<b>Insulation Support</b>
	Applies To	<b>Wire/Cable</b>
Configuration Features	Paired	<b>No</b>
	Terminal Angle	<b>Straight</b>
Body Features	Plating Material	<b>Brass, Pre-Tin</b>
Contact Features	Terminal Orientation	<b>Flag</b>
	Contact Plating Material	<b>Pre-Tin</b>
Termination Features	Crimp Type	<b>F-Crimp</b>
Mechanical Attachment	Mating Retention Type	<b>Dimple</b>
Dimensions	Mating Tab Width	<b>2.79 mm [ .11 in ]</b>
	Mating Tab Thickness	<b>.8 mm [ .032 in ]</b>
	Wire Insulation Diameter	<b>1.65 – 2.54 mm [ .065 – .1 in ]</b>
	Wire Size (AWG)	<b>22 – 18</b>
	Wire Size (mm <sup>2</sup> )	<b>.3 – .8</b>
	Material Thickness	<b>.25 mm [ .01 in ]</b>
	Overall Length	<b>11.68 mm [ .46 in ]</b>
Industry Standards	UL Rating	<b>Listed</b>
	CSA Certified	<b>Yes</b>
Packaging Features	Packaging Method	<b>Reel</b>
	Packaging Quantity	<b>8000</b>
Product Compliance	<a href="#">Statement of Compliance</a> PDF <a href="#">VIEW ALL PRODUCT COMPLIANCE</a>	


## CUSTOMERS ALSO BOUGHT

[CRIMP QUICK DISCONNECTS](#)
[RECTANGULAR CONNECTOR](#)
[POWER CONTACTS](#)
[STANDARD POWER RELAYS](#)

CRIMP QUICK DISCONNECTS



187 FLG FAST RCPT 20-16  
TPBR  
62591-1

 Save to List

 Find Similar Products

RECTANGULAR CONNECTOR  
SEALS



MINI UMNL CAVITY PLUG  
SEAL  
794995-1

 Save to List

 Find Similar Products

POWER CONTACTS



MINI UMNL SOCK 26-22  
AWG SN  
770902-1

 Save to List

 Find Similar Products

STANDARD POWER RELAYS



RT444012  
RT444012

 Save to List

 Find Similar Products

