



QUICK DISCONNECTS



TE CONNECTIVITY (TE) 110 PB FAST RCPT 22-18 TPBR FASTON | 110

62003-2
TE Internal Number: 62003-2

Always EU RoHS/ELV Compliant

Mating Tab Width **2.79 mm [.11 in]**

Mating Tab Thickness **.51 mm [.02 in]**

Wire Insulation Diameter **1.52 – 2.54 mm [.06 – .1 in]**

Wire Size (AWG) **22 – 18**

Wire Size (mm²) **.3 – .8**

Active

PRODUCT DRAWING
English

3D PDF

Product Drawings

RECEPTACLE, FASTON, PIGGYBACK, 2.79 [.110] SERIES

PDF
English

CAD Files

3D PDF

PDF
3D

Customer View Model

3D_IGS.ZIP
English

Customer View Model

3D_STP.ZIP
English

Customer View Model

2D_DXF.ZIP
English

Catalog Pages/Data Sheets

82004 FASTON Terminals (Insulated And Uninsulated) Catalog - FASTON Receptacles Section

PDF
English

FASTON_FASTON_Product_Line

PDF
English

Product Specifications

Application Specification

FASTON Piggyback Receptacles

PDF
English

Wire Preparation And Crimp Inspection Guide

PDF
English

Wire Preparation And Crimp Inspection Guide

TIF
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features	Insertion Force	Normal
	FASTON	Yes
	Wire/Cable Composition	Stranded
	Insulated	No
	Insulated Wire Support	No
	Support Style	Insulation Support
	Applies To	Wire/Cable

Configuration Features	Paired	No
	Terminal Angle	Straight
	Connection Capacity	Single

Body Features	Plating Material	Brass, Tin
	Plating Thickness (µin)	40

Contact Features	Terminal Orientation	Straight
	Contact Plating Material	Tin

Termination Features	Crimp Type	F-Crimp
----------------------	------------	----------------

Mechanical Attachment	Mating Retention Type	Dimple
-----------------------	-----------------------	---------------

Dimensions	Mating Tab Width	2.79 mm [.11 in]
	Mating Tab Thickness	.51 mm [.02 in]
	Wire Insulation Diameter	1.52 – 2.54 mm [.06 – .1 in]
	Wire Size (AWG)	22 – 18
	Wire Size (mm ²)	.3 – .8
	Material Thickness	.25 mm [.01 in]
	Overall Length	15.24 mm [.6 in]

Industry Standards	UL Rating	Listed
	CSA Certified	Yes





Packaging Features	Packaging Method	Reel
--------------------	------------------	-------------

Product Compliance

[Statement of Compliance](#)
PDF

[VIEW ALL PRODUCT COMPLIANCE](#)

CUSTOMERS ALSO BOUGHT

SPLICES	CRIMP QUICK DISCONNECTS	CRIMP QUICK DISCONNECTS	CRIMP RINGS & SPADES
 <p data-bbox="151 739 343 817">PG BUTT SPLC 22-16COMM22-18MIL 2-34067-1</p> <p data-bbox="151 896 383 963">Save to List Find Similar Products</p>	 <p data-bbox="462 739 710 817">FF 110 TAB 0.5-1.0MM2 PTPPB 160887-4</p> <p data-bbox="462 896 694 963">Save to List Find Similar Products</p>	 <p data-bbox="774 739 1021 817">PCB 110 TAB FLAG .031 TPBR LP 1-725996-2</p> <p data-bbox="774 896 1005 963">Save to List Find Similar Products</p>	 <p data-bbox="1085 739 1340 817">TERMINAL, PIDG SPD 16-14 8 32056</p> <p data-bbox="1085 896 1316 963">Save to List Find Similar Products</p>