



RJ45 CONNECTORS



Active

PRODUCT DRAWING
English

3D PDF

TE CONNECTIVITY (TE)

LED STK MJ ASSY, 2X4, 8 POS, CAT5

LE , Mini PCI

6339082-3

TE Internal Number: 6339082-3

Always EU RoHS/ELV Compliant

Port Configuration **Stacked**

Shielded **Yes**

Jack Configuration **2 x 4**

Connector Style **Jack**

Inverted Jack Face **No**

Product Drawings

ASSEMBLY, STACKED JACK, 2 X 4, 8 POSITION, SHIELDED, PANEL GROUND, LED, CATEGORY

PDF (TIFF AVAILABLE)
English

ASSEMBLY, STACKED JACK, 2 X 4, 8 POSITION, SHIELDED, PANEL GROUND, LED, CATEGORY

PDF (TIFF AVAILABLE)
English

CAD Files

3D PDF

PDF
3D

Customer View Model

2D_DXF.ZIP
English

Customer View Model

3D_IGS.ZIP
English

Customer View Model

3D_STP.ZIP
English

Product Specifications

Product Specification

High Performance Modular Plugs & Jacks, PCB Mounted

PDF
English

Application Specification

Modular Jacks

PDF
English

Product Environmental Compliance

TE Material Declaration

MD_6339082-3_12122015134_dmtec

PDF
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features	Shielded	Yes
	Connector Style	Jack
	Performance Category	Cat 5
	Profile	Low
	PCB Mounting Orientation	Side Entry (Right Angle)
	Connector Type	Connector Assembly
	Applies To	Printed Circuit Board
	Product Type	Connector
	Jack Type	RJ45
	Grounding Options	Panel Ground and PCB Ground
	LED	With
	Panel Stops	Without





Configuration Features	Port Configuration	Stacked
	Jack Configuration	2 x 4
	Number of Positions	8
	Terminals per Port	8
	Number of PCB Ground Tabs	6
	Preloaded	Yes
	Keyed	No

Body Features	Inverted Jack Face	No
	LED Color (Top Right)	Yellow
	Shield Material	Copper Alloy
	Grounding Tab Plating Material	Tin over Nickel
	Color	Black
	LED Color (Top Left)	Green
	Shield Plating Material	Tin over Nickel
	LED Color (Bottom Right)	Yellow
	LED Color (Bottom Left)	Green

Contact Features	Number of Contacts Loaded	8
	Solder Tail Contact Plating Material	Tin over Nickel
	Contact Base Material	Phosphor Bronze

	PCB ACTION PIN Grounds	Without
	Contact Mating Area Plating Material	Gold
	Contact Mating Area Plating Thickness (µm)	1.27
Termination Features	Grounding Clips	Without
	Termination Method to PC Board	Solder
Mechanical Attachment	PCB Mounting Style	Through Hole
	Panel Mount Retention	Without
Housing Features	Housing Material	PBT Polyester
	Housing Color	Black
Dimensions	Height (mm)	27.31
	PCB Thickness (Recommended)	1.57 mm [.062 in]
	PCB Tail Length	2.85 mm [.112 in]
Industry Standards	UL Flammability Rating	UL 94V-0
Packaging Features	Packaging Quantity	15
	Packaging Method	Package
Product Compliance	Statement of Compliance PDF VIEW ALL PRODUCT COMPLIANCE	

CUSTOMERS ALSO BOUGHT

SURFACE MOUNT RESISTORS	FPC CONNECTORS	WIRE-TO-BOARD CONNECTOR HOUSINGS	PCB D-SUB CONNECTORS
 <p>SMW3 12R 5% SMW312RJT</p> <p>Save to List Find Similar Products</p>	 <p>1MM FPC HORZ.TOP CONT.ASSY 30P 3-84953-0</p> <p>Save to List Find Similar Products</p>	 <p>2.0mm, HSG, 10pos 1-440129-0</p> <p>Save to List Find Similar Products</p>	 <p>HD-20 RCPT 9P VERT FFSCRLK 5745076-4</p> <p>Save to List Find Similar Products</p>

