



RJ45 CONNECTORS



TE CONNECTIVITY (TE)

2X4 OFFSET STK MJ,SHLD,G/Y LED&GND

LE , Mini PCI

6368062-4

TE Internal Number: 6368062-4

Always EU RoHS/ELV Compliant

Port Configuration **Stacked**

Shielded **Yes**

Jack Configuration **2 x 4**

Connector Style **Jack**

Inverted Jack Face **No**

Active

PRODUCT DRAWING
English

3D PDF

Product Drawings

[STACKED MODULAR JACK ASSEMBLY, 2x4 OFFSET, WITH LEDS, 8 POSN, RJ45](#)

PDF
English

CAD Files

[3D PDF](#)

PDF
3D

[Customer View Model](#)

2D_DXF.ZIP
English

[Customer View Model](#)

3D_IGS.ZIP
English

[Customer View Model](#)

3D_STP.ZIP
English

Product Specifications

Product Specification

[High Performance Modular Plugs & Jacks, PCB Mounted](#)

PDF
English

Application Specification

[Modular Jacks](#)

PDF
English

Product Environmental Compliance

TE Material Declaration

[MD_6368062-4_09262011024](#)

PDF
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features	Shielded	Yes
	Connector Style	Jack
	Performance Category	Cat 5
	Profile	Offset - Overhangs PCB, Very Low
	PCB Mounting Orientation	Side Entry (Right Angle)
	Connector Type	Connector Assembly
	Product Type	Connector
	Jack Type	RJ45
	Grounding Options	Panel Ground and PCB Ground
	LED	With
Panel Stops	Without	
Configuration Features	Port Configuration	Stacked
	Jack Configuration	2 x 4
	Number of Positions	8
	Terminals per Port	8
	Number of PCB Ground Tabs	7
	Preloaded	Yes
	Keyed	No
	Number of Grounding Clips	4
Body Features	Inverted Jack Face	No
	LED Color (Top Right)	Green/Yellow
	Shield Material	Copper Alloy
	Grounding Tab Plating Material	Tin over Copper
	Color	Black
	LED Color (Top Left)	Green/Yellow
	Shield Plating Material	Tin over Copper
	LED Color (Bottom Right)	Green/Yellow
LED Color (Bottom Left)	Green/Yellow	
Contact Features	Number of Contacts Loaded	8
	Solder Tail Contact Plating Material	Tin over Nickel
	Contact Base Material	Phosphor Bronze
	PCB ACTION PIN Grounds	Without
	Contact Mating Area Plating Material	Gold
	Contact Mating Area Plating Thickness (µin)	50

Termination Features	Grounding Clips	With
	Termination Method to PC Board	Through Hole - Press-Fit
Mechanical Attachment	PCB Mounting Style	Through Hole
	Panel Mount Retention	Without
Housing Features	Housing Material	PBT Polyester
	Housing Color	Black
Dimensions	PCB Thickness (Recommended)	1.57 mm [.062 in]
	PCB Tail Length	4.35 mm [.171 in]
Industry Standards	UL Flammability Rating	UL 94V-0
Packaging Features	Packaging Quantity	20
	Packaging Method	Tray
Product Compliance	Statement of Compliance PDF VIEW ALL PRODUCT COMPLIANCE	

CUSTOMERS ALSO BOUGHT

MULTIPLE CONFIGURATION PCB HEADERS & RECEPTACLES

10 SYS50 SMT HDR DR SHD SN
5-147377-1

Save to List
 Find Similar Products

RJ45 CONNECTORS

2X1 OFFSET MJ, LED(G/Y, G/Y)12PN
6368168-4

Save to List
 Find Similar Products

RJ45 CONNECTORS

MJ ASSY, 4P, 8POS, SH, CAT5, NS P/O
5406203-3

Save to List
 Find Similar Products

SURFACE MOUNT RESISTORS

RP 1J 140K 0.1% 15PPM CUT LENGTH
RP73D1J140KBTDG

Save to List
 Find Similar Products