




QUICK DISCONNECTS



Active

PRODUCT DRAWING
English

3D PDF

TE CONNECTIVITY (TE)

RECEPT, PIDG FASTON 22-18 187

FASTON | FASTON Terminals

640917-1

TE Internal Number: 640917-1
Alias ID: AMPS-0-0640917-1, F55918-000

Always EU RoHS/ELV Compliant

Mating Tab Width **4.75 mm [.187 in]**

Mating Tab Thickness **.51 mm [.02 in]**

Wire Insulation Diameter (Max) **3.43 mm [.135 in]**

Wire Size (AWG) **22 – 18**

Wire Size (CMA) **509 – 1900**

Product Drawings

[RECEPTACLE, 187 SERIES, FASTON , PIDG, WIRE SIZE: 22-18 AWG](#)

PDF
English

CAD Files

[Customer View Model](#)

2D_DXF.ZIP
English

[Customer View Model](#)

3D_IGS.ZIP
English

[Customer View Model](#)

3D_STP.ZIP
English

[3D PDF](#)

PDF
English

Catalog Pages/Data Sheets

[PIDG_FASTON](#)

PDF
English

[Ultra-Fast And Ultra Fast Plus](#)

PDF
English

[1773464-1_QRG_PIDG_TERMINALS_AND_SPLICES](#)

PDF
English

Product Specifications

Application Specification

[Pre-Insulated Diamond Grip \(PIDG\) FASTON Receptacle Contacts](#)

PDF
English

Product Environmental Compliance

TE Material Declaration

[MD_640917-1_062520131019_dmtec](#)

PDF
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features	Wire Stop	Yes
	Disconnect Type	Quick Disconnect Pin
	Insertion Force	Normal
	FASTON	Yes
	Wire/Cable Composition	Stranded
	Insulated	Yes
	Insulated Wire Support	Yes
	Support Style	Insulation Support
Applies To	Wire/Cable	
Configuration Features	Paired	No
	Terminal Angle	Straight
Electrical Characteristics	Voltage (Max) (V)	300
Body Features	Plating Material	Tin
	Fully Insulated	No
	Insulation Material	Nylon
Contact Features	Terminal Orientation	Straight
	Contact Plating Material	Tin
Termination Features	Crimp Type	F-Crimp
Mechanical Attachment	Mating Retention Type	Dimple
Dimensions	Mating Tab Width	4.75 mm [.187 in]
	Mating Tab Thickness	.51 mm [.02 in]
	Wire Insulation Diameter (Max)	3.43 mm [.135 in]
	Wire Size (AWG)	22 – 18
	Wire Size (CMA)	509 – 1900
	Wire Size (mm ²)	.32 – .82
	Material Thickness	.41 mm [.016 in]





	Overall Length	20.356 mm [.8 in]
Usage Conditions	Operating Temperature Range (°C)	105
Industry Standards	CSA Certified	Yes
	RU (UL Component Program)	Approved
Packaging Features	Packaging Method	Loose Piece
	Packaging Quantity	1000
Other	Barrel Color	Red

Product Compliance

[Statement of Compliance PDF](#)

[VIEW ALL PRODUCT COMPLIANCE](#)

CUSTOMERS ALSO BOUGHT

<p>CRIMP QUICK DISCONNECTS</p>  <p>RECEPT, PIDG FASTON 22-18 110 640925-2</p> <p>Save to List</p> <p>Find Similar Products</p>	<p>PADDLE & ROCKER SWITCHES</p>  <p>PRASB2-16F-BBR00=POWER ROCKER PRASB2-16F-BBR00</p> <p>Save to List</p> <p>Find Similar Products</p>	<p>CRIMP QUICK DISCONNECTS</p>  <p>RECEPT, PIDG FASTON 16-14 187 640919-1</p> <p>Save to List</p> <p>Find Similar Products</p>	<p>RECTANGULAR POWER CONNECTORS</p>  <p>9 POS MATE-N-LOK S 1-171197-0</p> <p>Save to List</p> <p>Find Similar Products</p>
---	--	---	---