

Active

PRODUCT DRAWING
Japanese

3D PDF

TE CONNECTIVITY (TE)

SUPER SEAL 26POS CAP ASSY V AU

6473418-1

TE Internal Number: 6473418-1

Always EU RoHS/ELV Compliant

Pin Diameter **1 mm [.039 in]**

Pitch **3 mm [.118 in]**

Number of Circuits **26**

Sealed **Yes**

Mounting Orientation **Vertical/180°**

Product Drawings

[WATER SEALED CONNECTOR CAP HOUSING 26POS ASSEMBLY](#)

PDF (TIFF AVAILABLE)

Japanese

[WATER SEALED CONNECTOR CAP HOUSING 26POS ASSEMBLY](#)

PDF (TIFF AVAILABLE)

Japanese

[WATER SEALED CONNECTOR CAP HOUSING 26POS ASSEMBLY](#)

PDF (TIFF AVAILABLE)

Japanese

CAD Files

[Customer View Model](#)

2D_DXF.ZIP

English

[3D PDF](#)

PDF

3D

[Customer View Model](#)

3D_IGS.ZIP

English

[Customer View Model](#)

3D_STP.ZIP

English

Product Specifications

Product Specification

[SUPER SEAL CONNECTOR](#)

PDF

Japanese

Instruction Sheets

Instruction Sheet (non U.S.)

[SUPER SEAL CONNECTOR PLUG HOUSING CONNECTOR](#)

PDF

English

[SUPER SEAL CONNECTOR PLUG HOUSING CONNECTOR](#)

TIF

English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features	Sealed	Yes
	Hybrid Header	No
	Shielded	No

Configuration Features	Number of Circuits	26
	Number of Rows	4
	Number of Sections	1
	Number of Signal Positions	26

Electrical Characteristics	Nominal Voltage Architecture (V)	12, 24, 240
	Voltage Rating (Max)	250 VAC [250 VDC]
	Operating Voltage	250 VAC [250 VDC]

Body Features	Color	Black
---------------	-------	--------------

Contact Features	Pin Diameter	1 mm [.039 in]
	Circuit Application	Signal
	Interface Plating	Gold (Au)

Termination Features	Termination Method	Through Hole - Solder
----------------------	--------------------	------------------------------

Mechanical Attachment	Mounting Orientation	Vertical/180°
	PCB Mount Retention	Without
	Panel Mount Retention	Without
	Mounting Holes	With
	PCB Mount Alignment	With
	Locking Interface	With

Housing Features	Pitch	3 mm [.118 in]
------------------	-------	-------------------------

Dimensions	Profile Height from PCB	24.7 mm [.972 in]
	Width	39 mm [1.535 in]
	Length	36.5 mm [1.437 in]

Usage Conditions	Operating Temperature (Max) (°C)	65, 70, 75, 80, 85, 90, 100, 105, 110, 120, 125
	Operating Temperature (Max) (°F)	149, 158, 167, 176, 185, 194, 212, 221, 230, 248, 257
	Operating Temperature Range	-40 – 125 °C [-40 – 257 °F]

Industry Standards	UL Flammability Rating	UL 94V-0
--------------------	------------------------	-----------------













Packaging Features	Packaging Type	Tube
--------------------	----------------	-------------

Product Compliance

[Statement of Compliance](#)
PDF

[VIEW ALL PRODUCT COMPLIANCE](#)

CUSTOMERS ALSO BOUGHT

AUTOMOTIVE, TRUCK, BUS, & OFF-ROAD HEADERS	THROUGH-HOLE RESISTORS	SURFACE MOUNT RESISTORS	SURFACE MOUNT RESISTORS
 <p>SUPER SEAL 26POS CAP ASSY V AU 6473418-2</p>	 <p>SQB20 15R 5% (WIRE) SQBW2015RJ</p>	 <p>RN 0805 205K 0.1% 10PPM 1K RL RN73C2A205KBTF</p>	 <p>CPF 0402 64K9 0.1% 25PPM 1K RL CPF0402B64K9E1</p>
<p> Save to List</p> <p> Find Similar Products</p>	<p> Save to List</p> <p> Find Similar Products</p>	<p> Save to List</p> <p> Find Similar Products</p>	<p> Save to List</p> <p> Find Similar Products</p>