




## POWER CONTACTS



✓ Active

↓ **PRODUCT DRAWING**  
English

↓ **3D PDF**

TE CONNECTIVITY (TE)

### III+ SKT,24-20,30AU/FL,STRIP

AMP | Type III+

66331-8

TE Internal Number: 66331-8

Alias ID: 1098628, 1099392

Always EU RoHS/ELV Compliant

Product Type **Contact**

Wire/Cable Size (AWG) **24 – 20**

Wire/Cable Size (mm<sup>2</sup>) **.2 – .6**

Circuit Application **Signal**

Contact Type **Socket**

#### Product Drawings

[SOCKET ASSEMBLY, .062, TYPE III+](#)

PDF  
English

#### CAD Files

[Customer View Model](#)

2D\_DXF.ZIP  
English

[3D PDF](#)

PDF  
3D

[Customer View Model](#)

3D\_IGS.ZIP  
English

[Customer View Model](#)

3D\_STP.ZIP  
English

#### Catalog Pages/Data Sheets

[Signal Contacts](#)

PDF  
English

[AMP Circular Connectors For Commercial Signal & Power Applications](#)

PDF  
English

[M\\_SERIES\\_PIN\\_AND\\_SOCKET\\_CONNECTORS](#)

PDF  
English

#### Product Specifications

Application Specification

[Type III+ \(Size 16\) Contacts](#)

PDF  
English

#### Product Environmental Compliance

TE Material Declaration

[MD\\_66331-8\\_04092014033\\_dmtec](#)

PDF  
English

---

## Instruction Sheets

Instruction Sheet (U.S.)

[Selection Of Multimate Pin And Socket Contacts](#)

PDF  
English

[Selection Of Multimate Pin And Socket Contacts](#)

PDF  
Japanese

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

---

Product Type Features	Product Type	Contact
Electrical Characteristics	Test Current (A)	<b>13</b>
Contact Features	Contact Type	<b>Socket</b>
	Contact Base Material	<b>Brass</b>
	Contact Mating Area Plating Material	<b>Gold</b>
	Contact Mating Area Plating Thickness (µin)	<b>30</b>
	Contact Termination Area Plating Material	<b>Gold Flash</b>
	Contact Size	<b>16</b>
Termination Features	Wire/Cable Size (AWG)	<b>24 – 20</b>
	Wire/Cable Size (mm <sup>2</sup> )	<b>.2 – .6</b>
	Termination Type	<b>Crimp</b>
Dimensions	Accepts Wire Insulation Diameter Range	<b>2.03 – 2.54 mm [ .08 – .1 in ]</b>
Operation/Application	Circuit Application	<b>Signal</b>
Packaging Features	Packaging Method	<b>Reel</b>
	Packaging Quantity	<b>4000</b>
Other	Comment	<b>Overall insulation crimp diameter, including crimp barrel, must not exceed 3.18 [125].</b>
	For Use With	<b>CPC Connectors, G Series Connectors, M Series Connectors</b>
	Wire/Cable Type	<b>Discrete Wire</b>


---

Product Compliance

[Statement of Compliance](#)

PDF

## CUSTOMERS ALSO BOUGHT

RECTANGULAR CONNECTOR HOUSINGS	CIRCULAR POWER CONNECTORS	PCB D-SUB CONNECTORS	POWER CONTACTS
			
<p>HSG, PLUG, 4 POSN, SM METRIC 207015-1</p>	<p>CPC PLUG ASSY, SRS 6, SZ 17-10 213906-1</p>	<p>25 MSFL PLUG RA 590 (SL, FM, BL) 5747834-6</p>	<p>III+ PIN, 24-20, 30AU/FL, STRIP 66332-8</p>
<p> Save to List  Find Similar Products</p>	<p> Save to List  Find Similar Products</p>	<p> Save to List  Find Similar Products</p>	<p> Save to List  Find Similar Products</p>