QUICK DISCONNECTS



✓ Active



TE CONNECTIVITY (TE) .250 RECP WITH DBL TAB

FASTON | FASTON Terminals and Housings

726308-1 TE Internal Number: 726308-1

Always EU RoHS/ELV Compliant

Mating Tab Width 6.35 mm [.25 in]

Mating Tab Thickness .81 mm [.032 in]

Plating Material **Unplated**

Disconnect Type **Quick Disconnect Pin**

Crimp Type F-Crimp

Product Drawings	RECEPTACLE .250 SERIES WITH DOUBLE TAB Steckaufnahme .250 Serie M.Dopp.Tabaufnahme PDF English
CAD Files	Customer View Model 3D_IGS.ZIP English
	Customer View Model 3D_STP.ZIP English
	Customer View Model 2D_DXF.ZIP English
	3D PDF PDF English
Catalog Pages/Data Sheets	FASTON Tabs PDF English
Product Environmental Compliance	
TE Material Declaration	MD_726308-1_0522201530_dmtec PDF English

Please review product documents or contact us for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features

Disconnect Type

Quick Disconnect Pin

FASTON

Yes

Ƴ ⊡ f v

	Wire/Cable Composition	Stranded
	Wire/Cable Type	Discrete Wire
	Insulated Wire Support	No
	Applies To	Wire/Cable
Configuration Features	Paired	Νο
	Stud Hole	Νο
	Terminal Angle	15°, 66°
Body Features	Plating Material	Unplated
Contact Features	Terminal Orientation	Straight
Termination Features	Crimp Type	F-Crimp
Dimensions	Mating Tab Width	6.35 mm [.25 in]
	Mating Tab Thickness	.81 mm [.032 in]
Packaging Footures	Packaging Mathed	Вох
Packaging Features	Packaging Method	
	Packaging Quantity	1000
Product Compliance	Statement of Compliance	
Froduct Compliance	Statement of Compliance PDF	
	VIEW ALL PRODUCT COMPLIANCE	

CUSTOMERS ALSO BOUGHT

SPLICES	MOTOR TERMINAL HOUSINGS	CRIMP RINGS & SPADES	SPLICES	
	2			
SPLICE, PG BUTT 12-10 34072	.250 S CIR FAST HSG NAT 1-480416-0	TERM, PG RING 12-10 1/4 55678-1	SPLICE, CE, 22-12 329251	>
🔁 Save to List	Save to List	5 Save to List	Save to List	
Find Similar Products	Find Similar Products	5 Find Similar Products	5 Find Similar Products	