

RECTANGULAR POWER CONNECTORS



TE CONNECTIVITY (TE) 04P UMNLII IN-LNE PLUG HSG KIT

MATE-N-LOK | Universal MATE-N-LOK

770019-1 TE Internal Number: 770019-1 Alias ID: 1177339

Number of Positions 4

Always EU RoHS/ELV Compliant

Product Type **Housing** Housing Type **Plug** Connector System **Wire-to-Wire** Applies To **Wire/Cable**

PRODUCT DRAWING
 English
 3D PDF

| Product Drawings | PLUG HOUSING KIT, 4 CIRCUIT, IN-LINE, UNIVERSAL MATE-N-LOK ^{PDF} English |
|---------------------------|---|
| CAD Files | Customer View Model 2D_DXF.ZIP English |
| | 3D PDF PDF 3D |
| | Customer View Model 3D_IGS.ZIP English |
| | Customer View Model 3D_STP.ZIP English |
| Catalog Pages/Data Sheets | SOFT_SHELL_PIN_SOCKET_CONNECTORS_STANDARD_DENSITY PDF English |
| Product Specifications | |
| Product Specification | Connector, Universal MATE-N-LOK II PDF English |
| Application Specification | Circular Multi-Pin Connector ^{PDF} English Universal MATE-N-LOK II Connectors |
| | PDF English |

Product Environmental Compliance

TE Material Declaration

MD_770019-1_06182014231_dmtec PDF English y ii f v

Instruction Sheets

Instruction Sheet (U.S.)

Universal MATE-N-LOK Connectors PDF English

Please review product documents or **contact us** for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

| Product Type Features | Product Type | Housing |
|----------------------------|------------------------------|-----------------------------|
| | Housing Type | Plug |
| | Contact Type | Pin or Socket |
| | | |
| Configuration Features | Number of Positions | 4 |
| | Centerline | 6.35 mm [.25 in] |
| | Number of Rows | 1 |
| | Multiple Contact Types | Without |
| | Contact Layout | Inline |
| | , | |
| Electrical Characteristics | Operating Voltage (VAC) | 600 |
| Contact Features | Contact Retention | Without |
| Mechanical Attachment | Assembly Integration Feature | Without |
| Housing Features | UL Flammability Rating | UL 94V-0 |
| | Housing Color | White |
| | Housing Material | Nylon GF |
| Dimensions | Width (mm) | 22.99 |
| | Length (mm) | 26.67 |
| Usage Conditions | Sealed Condition | Not Sealed |
| Operation/Application | Connector System | Wire-to-Wire |
| | Applies To | Wire/Cable |
| | Operating Temperature | -55 – 105 °C [-67 – 221 °F] |
| | | |

| | UL Rating | Recognized |
|--------------------|-----------------------------|---------------------------------|
| | CSA File Number | LR7189 |
| | Agency/Standard | CSA, UL |
| | VDE Tested | Yes |
| | CSA Rating | Certified |
| | Agency/Standard Number | E28476 |
| | | |
| Packaging Features | Packaging Method | Package |
| | Packaging Quantity | 1 |
| | | |
| Other | For Use With | Universal MATE-N-LOK Connectors |
| Product Compliance | Statement of Compliance | |
| | PDF | |
| | VIEW ALL PRODUCT COMPLIANCE | |

CUSTOMERS ALSO BOUGHT

| CRIMP QUICK DISCONNECTS | POWER CONTACTS | RECTANGULAR POWER CONNECTORS | RECTANGULAR POWER CONNECTORS |
|--|---|---|--|
| es | and the second second | and and a second | 5000 L |
| 187 FASTON FLG, RCEP, 18-14 014T 1742422-1 | UMNL II SOK PTPPHBZ LP 24-18 770253-3 | 04P UMNL II PLUG REAR 94VO 770036-1 | 04P UMNL II PLUG-FRONT 94VO 770035-1 |
| Save to List | Save to List | Save to List Find Similar Products | Save to List |
| 1 | | | |

| Products - 72 Results | | View All | Compare 0/10 🗢 |
|---|--|---|-------------------------|
| Relation Type | • | | |
| RELATIONSHIP Mating Products Used to identify Mating Parts | | | See All Mating Products |
| | PRODUCT - MATING PRODUCTS Connectors - Rectangular Power Connectors Elcon I High Current Socket Headers SKT HEADER, RIGHT | Always EU RoHS/ELV Complia Product Type Header | ant |





✓ Active

Housing Type **Receptacle** Connector System **Wire-to-Board** Applies To **Printed Circuit Board** Contact Current Rating **36 A**

RELATIONSHIP

Contacts

Identifies Contacts compatible with a given Housing



PRODUCT - CONTACTS

Connectors - Power Contacts Elcon I High Current Contacts PIN, 2MM, 12-14 AWG - 193841-1 TE INTERNAL NUMBER: 193841-1 ALIAS ID: AMP-0-0193841-1, CL3861-000

✓ Active

Always EU RoHS/ELV Compliant

Product Type **Contact** Contact Current Rating **32 A** Operating Voltage **600 VAC** Wire/Cable Size **14 – 12 AWG** Wire/Cable Size **2.08 – 3.31 mm**²

RELATIONSHIP **Mating Products** Used to identify Mating Parts



PRODUCT - MATING PRODUCTS

Connectors - Rectangular Power Connectors MATE-N-LOK I Universal MATE-N-LOK 04P UMNL HDR ASSY

R/A 94VO LF - 3-643230-0 TE INTERNAL NUMBER: 3-643230-0

✓ Active

See All Mating Products

See All Contacts

Always EU RoHS/ELV Compliant

