



CONNECTORS

## RECTANGULAR POWER CONNECTORS



TE CONNECTIVITY (TE)

### 12P .093 COMM P&S PLUG

[Commercial Pin & Socket](#) | [Commercial Pin and Socket Connectors](#)

770102-1

TE Internal Number: 770102-1

[Always EU RoHS/ELV Compliant](#)

Product Type **Housing**

Housing Type **Plug**

Connector System **Wire-to-Wire**

Applies To **Wire/Cable**

Number of Positions **12**

✓ Active

↓ **PRODUCT DRAWING**  
English

↓ **3D PDF**



#### Product Drawings

[PLUG, 12 CIRCUIT, .093 COMMERCIAL PIN AND SOCKET](#)

PDF ([TIFF AVAILABLE](#))  
English

[PLUG, 12 CIRCUIT, .093 COMMERCIAL PIN AND SOCKET](#)

PDF ([TIFF AVAILABLE](#))  
English

#### CAD Files

[Customer View Model](#)

3D\_IGS.ZIP  
English

[Customer View Model](#)

3D\_STP.ZIP  
English

[Customer View Model](#)

2D\_DXF.ZIP  
English

[3D PDF](#)

PDF  
English

#### Catalog Pages/Data Sheets

[SOFT\\_SHELL\\_PIN\\_SOCKET\\_CONNECTORS\\_STANDARD\\_DENSITY](#)

PDF  
English

## Product Specifications

Product Specification	<a href="#">.093 Diameter Commercial Pin And Socket Connector</a> PDF English
Application Specification	<a href="#">.093 Diameter Pin And Socket Contacts And Housings</a> PDF English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features	Product Type	<b>Housing</b>
	Housing Type	<b>Plug</b>
	Contact Type	<b>Pin or Socket</b>
Configuration Features	Number of Positions	<b>12</b>
	Centerline	<b>5.03 mm [ .198 in ]</b>
	Number of Rows	<b>4</b>
	Row-to-Row Spacing	<b>5.03 mm [ .198 in ]</b>
	Contact Layout	<b>Matrix</b>
Electrical Characteristics	Operating Voltage (VAC)	<b>250</b>
Mechanical Attachment	Panel Mount Retention	<b>Without</b>
Housing Features	UL Flammability Rating	<b>UL 94V-2</b>
	Housing Color	<b>Natural</b>
	Housing Material	<b>Nylon 6/6</b>
Dimensions	Width (mm)	<b>18.67</b>
	Height (mm)	<b>24.64</b>
	Length (mm)	<b>24.64</b>
Usage Conditions	Sealed Condition	<b>Not Sealed</b>
Operation/Application	Connector System	<b>Wire-to-Wire</b>
	Applies To	<b>Wire/Cable</b>
	Operating Temperature	<b>-55 – 105 °C [ -67 – 221 °F ]</b>

Industry Standards	UL Rating	<b>Recognized</b>
	CSA Rating	<b>Certified</b>
	CSA File Number	<b>LR7189</b>
	Agency/Standard Number	<b>E28476</b>
	Agency/Standard	<b>CSA, UL</b>

---

Packaging Features	Packaging Method	<b>Package</b>
	Packaging Quantity	<b>1</b>

---

Other	For Use With	<b>Receptacle Housing</b>
-------	--------------	---------------------------

---

Product Compliance

[Statement of Compliance](#)  
PDF

[VIEW ALL PRODUCT COMPLIANCE](#)

