

HOUSINGS

















PRODUCT DRAWING English



3D PDF



MTA | SL-156

770849-5

TE CONNECTIVITY (TE)

Centerline 3.96 mm [.156 in]

Number of Positions **5**

TE Internal Number: 770849-5

Number of Rows 1

Color Natural

Mating Retention With

Product Drawings

HOUSING WITH LOCKING RAMP AND POLARIZING TABS, SL-156

05P SL156 HSG W/LCK RMP & HSG

PDF **English**

CAD Files

Customer View Model

3D_STP.ZIP English

3D PDF

PDF **3D**

Customer View Model

2D_DXF.ZIP English

Customer View Model

3D_IGS.ZIP **English**

Catalog Pages/Data Sheets

MTA, CST-100 II, SL-156 And AMP Economy Power (EP) Connectors

PDF **English**

Product Specifications

Product Specification Hooded SL 156 Connectors, Tin

PDF **English**

Hooded SL 156 Connectors, Gold

PDF **English**

SL 156 Connectors

PDF **English**

SL 156 Contacts And Housings

PDF **English**

Product Environmental Compliance

Application Specification

PDF **English**

Please review product documents or contact us for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features	Sealed	No
	Connector Type	Housing
	Applies To	Wire/Cable
	Connector Style	Receptacle
	Connector System	Wire-to-Board
	Strain Relief	Without
	Product Type	Connector
Configuration Features	Number of Positions	5
	Number of Rows	1
Electrical Characteristics	Operating Voltage	250 VAC
Body Features	Color	Natural
Contact Features	Contact Type	Socket
	Contact Current Rating (A)	6.5
	Contact Layout	Inline
Termination Features	Termination Method to Wire/Cable	Crimp
Mechanical Attachment	Mating Retention	With
	Mating Retention Type	Locking Ramp
	PCB Mount Retention	Without
	Panel Mount Retention	Without
	Mating Alignment	With
	Contact Retention	Without
	PCB Mount Alignment	Without
	Mating Alignment Type	Polarization
Housing Features	Centerline	3.96 mm [.156 in]

Hausing Calar

Matural

	Housing Style Housing Material	Standard Nylon - GF
Dimensions	Length (in)	.777
	Height (in)	.25
	Wire/Cable Size (AWG)	30 – 18
	Wire/Cable Size (mm²)	.0509 – .823
Usage Conditions	Operating Temperature Range	-55 – 105 °C [-67 – 221 °F]
Operation/Application	For Use With	SL .156 Contacts
Industry Standards	CSA File Number	LR 7189
	Agency/Standard	CSA, UL
	UL File Number	E28476
	UL Rating	Listed
	UL Flammability Rating	UL 94V-0
	CSA Rating	Certified
Packaging Features	Packaging Quantity	500
	Packaging Method	Bag/Box
Other	Comment	Unit Accepts 1.14[.045] Square or Round Post, Accepts Keying Plug 640254-1and 640255-1
Product Compliance	Statement of Compliance	

PDF

VIEW ALL PRODUCT COMPLIANCE

CUSTOMERS ALSO BOUGHT



