



CONNECTOR HOUSINGS



TE CONNECTIVITY (TE)

8 POS AMPSEAL PLUG ASSEMBLY

AMP | AMPSEAL

776286-1

TE Internal Number: 776286-1

Always EU RoHS/ELV Compliant

Connector Style **Housing for female terminals**

Mating Pin Diameter **1.3 mm [.051 in]**

Number of Positions **8**

Pitch **4 mm [.157 in]**

Sealed **Yes**

Active

PRODUCT DRAWING
English

3D PDF

Product Drawings

[PLUG ASSEMBLY, AMPSEAL FAMILY DRAWING](#)

PDF
English

CAD Files

[Customer View Model](#)

3D_IGS.ZIP
English

[Customer View Model](#)

3D_STP.ZIP
English

[Customer View Model](#)

2D_DXF.ZIP
English

[3D PDF](#)

PDF
3D

Product Specifications

Application Specification

[AMPSEAL Automotive Plug Connector And Header Assembly](#)

PDF
English





Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features

Connector Style	Housing for female terminals
Sealed	Yes
Hybrid Connector	No
Primary Locking Feature	Integrated in Housing
Connector System	Wire-to-Board/Device

	Row-to-Row Spacing	.157 mm [4 in]
	Strain Relief	No
Configuration Features	Number of Positions	8
	Number of Rows	3
Electrical Characteristics	Nominal Voltage Architecture (V)	12, 24, 42, 48, 80, 90, 125, 240
	Operating Voltage (VAC)	250
Body Features	Cable Exit Angle	180°
	Body Material	Other
	Color	Black
Contact Features	Mating Pin Diameter	1.3 mm [.051 in]
Mechanical Attachment	Terminal Position Assurance	Yes
	Mounting Feature	No
	Polarized	Yes
Housing Features	Pitch	4 mm [.157 in]
Dimensions	Width	33.6 mm [1.323 in]
	Height	34.6 mm [1.362 in]
	Length	27.4 mm [1.079 in]
Usage Conditions	Operating Temperature Range	-40 – 125 °C [-40 – 257 °F]
Industry Standards	Degree of Protection	IP6K9K
	UL Flammability Rating	UL 94V-0
Packaging Features	Packaging Method	Package
	Packaging Quantity	220
Other	Connector Position Assurance Capable	No
	Serviceable	Yes

CUSTOMERS ALSO BOUGHT

<p>AUTOMOTIVE, TRUCK, BUS, & OFF-ROAD HOUSINGS</p>  <p>RECEPTACLE HOUSING, 18 POSITIO 1326133-1</p> <p>Save to List Find Similar Products</p>	<p>AUTOMOTIVE, TRUCK, BUS, & OFF-ROAD HOUSINGS</p>  <p>AS 16, 4P CAP ASSY, RD, KEY 2 776536-2</p> <p>Save to List Find Similar Products</p>	<p>HEAT SHRINK COMPONENT ACCESSORIES</p>  <p>URHR-2 URHR-2</p> <p>Save to List Find Similar Products</p>	<p>AUTOMOTIVE, TRUCK, BUS, & OFF-ROAD HOUSINGS</p>  <p>23P AMPSEAL PLUG ASSY BLUE 770680-5</p> <p>Save to List Find Similar Products</p>
---	---	--	--

Products - 11 Results

View All

Compare 0/10


Relation Type

RELATIONSHIP

Mating Products

Used to identify Mating Parts

See All Mating Products

	<p>PRODUCT - MATING PRODUCTS</p> <p>Connectors - Automotive, Truck, Bus, & Off-Road Headers AMPI AMPSEAL</p> <p>8 POS RTANG HDR ASSY W/GASKET - 1-776280-1 TE INTERNAL NUMBER: 1-776280-1</p> <p>✓ Active</p> <p>Always EU RoHS/ELV Compliant</p> <p>Pin Diameter 1.3 mm</p> <p>Pitch 4 mm</p> <p>Number of Circuits 8</p> <p>Sealed Yes</p> <p>Mounting Orientation Horizontal/90°</p>
---	---

RELATIONSHIP

Cavity Plugs

Cavity Plugs

See All Cavity Plugs

	<p>PRODUCT - CAVITY PLUGS</p> <p>Connectors - Seals & Cavity Plugs AMPI AMPSEAL</p> <p>SEAL PLUG, AMPSEAL - 770678-1 TE INTERNAL NUMBER: 770678-1 ALIAS ID: AMP-0-0770678-1, EG9736-000</p> <p>Always EU RoHS/ELV Compliant</p> <p>Seal Type Cavity Blanking Plug</p> <p>Color Natural</p>
---	---

✓ Active

RELATIONSHIP

Mating Products

Used to identify Mating Parts

[See All Mating Products](#)

PRODUCT - MATING PRODUCTS



Connectors - Automotive, Truck, Bus, & Off-Road Headers
I AMPSEAL

8 POS RIGHT ANGLE HDR ASSY - 776279-1

TE INTERNAL NUMBER: 776279-1

✓ Active

Always EU RoHS/ELV Compliant

Pin Diameter **1.3 mm**

Pitch **4 mm**

Number of Circuits **8**

Sealed **Yes**

Mounting Orientation

Horizontal/90°

