



RECTANGULAR POWER CONNECTORS



TE CONNECTIVITY (TE)

09P MINI UMNL2 PLUG HSG UL94V0

MATE-N-LOK | Mini-Universal MATE-N-LOK 2

794194-1

TE Internal Number: 794194-1

Always EU RoHS/ELV Compliant

Product Type **Housing**

Housing Type **Plug**

Connector System **Wire-to-Wire**

Applies To **Wire/Cable**

Number of Positions **9**

Active

PRODUCT DRAWING
English

3D PDF

Product Drawings

[PLUG, 9 CIRCUIT, MINI UNIVERSAL MATE-N-LOK 2](#)

PDF (TIFF AVAILABLE)
English

[PLUG, 9 CIRCUIT, MINI UNIVERSAL MATE-N-LOK 2](#)

PDF (TIFF AVAILABLE)
English

CAD Files

[Customer View Model](#)

3D_IGS.ZIP
English

[Customer View Model](#)

3D_STP.ZIP
English

[Customer View Model](#)

2D_DXF.ZIP
English

[3D PDF](#)

PDF
English

Catalog Pages/Data Sheets

[SOFT_SHELL_PIN_AND_SOCKET_CONNECTORS_CATALOG](#)

PDF
English

Product Specifications

Application Specification

[Mini-Universal MATE-N-LOK 2 Connectors](#)

PDF
English

Product Environmental Compliance

TE Material Declaration

[MD_794194-1_05042012618](#)

PDF
English

Instruction Sheets

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features	Product Type	Housing
	Housing Type	Plug
	Contact Type	Socket
Configuration Features	Number of Positions	9
	Centerline	4.14 mm [.163 in]
	Number of Rows	3
	Row-to-Row Spacing	4.14 mm [.163 in]
	Contact Layout	Matrix
	Multiple Contact Types	Without
Electrical Characteristics	Operating Voltage (VAC)	600
	Operating Voltage (VDC)	600
Contact Features	Contact Retention	Without
Mechanical Attachment	Panel Mount Retention	Without
	Assembly Integration Feature	Without
Housing Features	UL Flammability Rating	UL 94V-0
	Housing Color	Natural
	Housing Material	Nylon
Usage Conditions	Sealed Condition	Not Sealed
Operation/Application	Connector System	Wire-to-Wire
	Applies To	Wire/Cable
	Operating Temperature	-55 – 105 °C [-67 – 221 °F]
Industry Standards	Glow Wire Rating	Standard Part - Not Glow Wire
	UL Rating	Recognized

Agency/Standard Number **E28476**





Agency/Standard **UL**

Packaging Features Packaging Method **Bag**
Packaging Quantity **400**

Other For Use With **Mini-Universal MATE-N-LOK 2 Cap Housing/PC Board Pin Headers Header**

Product Compliance [Statement of Compliance](#)
PDF
[VIEW ALL PRODUCT COMPLIANCE](#)

CUSTOMERS ALSO BOUGHT

MULTI-FUNCTION INLET FILTERS  PSOSOS000=C1007 PSOSOS000 Save to List Find Similar Products	HEAT SHRINK TUBING  V4-3/4-0-SP V4-3/4-0-SP Save to List Find Similar Products	POWER CONTACTS  MINI UMNL2 SOK 22-18 AWG SN LP 794229-1 Save to List Find Similar Products	SMA CONNECTORS  PLUG, SMA, HEX CRIMP COMM 5447647-1 Save to List Find Similar Products
---	---	--	--

Products - 40 Results

[View All](#)

[Compare 0/10](#)

Relation Type ▼

RELATIONSHIP

Contacts

Identifies Contacts compatible with a given Housing

[See All Contacts](#)



PRODUCT - CONTACTS

Connectors - Power Contacts
MATE-N-LOK I Mini-Universal MATE-N-LOK 2
MINI UMNL2 PIN 30-26AWG LP LF
- 1-794224-0
TE INTERNAL NUMBER: 1-794224-0

✓ Active

Always EU RoHS/ELV Compliant

Product Type **Contact**

Contact Current Rating **5 A**

Operating Voltage **600 VAC**

Operating Voltage **600 VDC**

Wire/Cable Size **30 – 26 AWG**

RELATIONSHIP

Contacts

Identifies Contacts compatible with a given Housing

[See All Contacts](#)

PRODUCT - CONTACTS



Connectors - Power Contacts
MATE-N-LOK I Mini-Universal MATE-N-LOK 2
MINI UMNL2 SCKT 20-16AWG LP SN - 794231-1
TE INTERNAL NUMBER: 794231-1

✓ Active

Always EU RoHS/ELV Compliant

Product Type **Contact**

Contact Current Rating **10.5 A**

Operating Voltage **600 VAC**

Operating Voltage **600 VDC**

Wire/Cable Size **20 – 16 AWG**



RELATIONSHIP

Contacts

Identifies Contacts compatible with a given Housing

[See All Contacts](#)

PRODUCT - CONTACTS



Connectors - Power Contacts
MATE-N-LOK I Mini-Universal MATE-N-LOK 2
MINI UMNL2 SOK 30-26 AWG SN - 794217-1
TE INTERNAL NUMBER: 794217-1

✓ Active

Always EU RoHS/ELV Compliant

Product Type **Contact**

Contact Current Rating **10.5 A**

Operating Voltage **600 VAC**

Operating Voltage **600 VDC**

Wire/Cable Size **30 – 26 AWG**

