



RECTANGULAR POWER CONNECTORS



TE CONNECTIVITY (TE)
2POS,MICRO MNL,RCPT HSG
[MATE-N-LOK](#) | [Micro MATE-N-LOK](#)

794617-2
TE Internal Number: 794617-2

Always EU RoHS/ELV Compliant

Product Type **Housing**

Housing Type **Receptacle**

Connector System **Wire-to-Board, Wire-to-Wire**

Applies To **Printed Circuit Board, Wire/Cable**

Number of Positions **2**

Active

[PRODUCT DRAWING](#)
English

[3D PDF](#)

Product Drawings

[RECEPTACLE HOUSING, 2 TO 24 POSITION,DUAL ROW, MICRO MATE-N-LOK](#)

PDF
English

CAD Files

[3D PDF](#)

PDF
3D

[Customer View Model](#)

2D_DXF.ZIP
English

[Customer View Model](#)

3D_IGS.ZIP
English

[Customer View Model](#)

3D_STP.ZIP
English

Catalog Pages/Data Sheets

[SOFT_SHELL_PIN_AND_SOCKET_CONNECTORS_CATALOG](#)

PDF
English

[1773458-4_MICRO_MATE_N_LOK_CONNECTOR_SYSTEM_ORG](#)

PDF
English

Product Specifications

Product Specification

[3 Mm Micro MATE-N-LOK Connector](#)

PDF
English

Application Specification

[Micro MATE-N-LOK Connectors](#)

PDF
English

Qualification Test Report

[3 Mm Micro MATE-N-LOK Connector](#)

PDF
English

Product Environmental Compliance

TE Material Declaration

[MD_794617-2_122820152120_dmtec](#)

PDF

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features	Product Type	Housing
	Housing Type	Receptacle
	Contact Type	Socket

Configuration Features	Number of Positions	2
	Centerline	3 mm [.118 in]
	Number of Rows	2
	Row-to-Row Spacing	3 mm [.118 in]

Electrical Characteristics	Operating Voltage (VAC)	250
----------------------------	-------------------------	------------

Housing Features	UL Flammability Rating	UL 94V-0
	Housing Color	Black
	Housing Material	Nylon 66/6

Operation/Application	Connector System	Wire-to-Board, Wire-to-Wire
	Applies To	Printed Circuit Board, Wire/Cable
	Operating Temperature	-40 – 105 °C [-40 – 221 °F]

Industry Standards	UL Rating	Recognized
	VDE Tested	Yes
	CSA Rating	Certified
	CSA File Number	LR7189
	Agency/Standard Number	E28476
	Agency/Standard	CSA, UL

Packaging Features	Packaging Method	Package
	Packaging Quantity	1

Product Compliance [Statement of Compliance](#)
PDF

[VIEW ALL PRODUCT COMPLIANCE](#)

Products - 56 Results

[View All](#)

[Compare 0/10](#)

Relation Type ▼

RELATIONSHIP

Mating Products

Used to identify Mating Parts

[See All Mating Products](#)

PRODUCT - MATING PRODUCTS



Connectors - Rectangular Power Connectors
MATE-N-LOK I Micro MATE-N-LOK

**02P MICRO MNL ASSY,
R/A, HDR LF - 3-794619-2**

TE INTERNAL NUMBER: 3-794619-2

✓ Active

Always EU RoHS/ELV Compliant



RELATIONSHIP

Mating Products

Used to identify Mating Parts

[See All Mating Products](#)

PRODUCT - MATING PRODUCTS



Connectors - Rectangular Power Connectors
MATE-N-LOK I Micro MATE-N-LOK

**02P MICRO MNL ASSY,
R/A, SMT LF - 3-794622-2**

TE INTERNAL NUMBER: 3-794622-2

✓ Active

Always EU RoHS/ELV Compliant




RELATIONSHIP

Mating Products

Used to identify Mating Parts

[See All Mating Products](#)

PRODUCT - MATING PRODUCTS



Connectors - Standard Rectangular
Connectors

MATE-N-LOK I Micro MATE-N-LOK

**02P MICRO MNL ASSY,
VRT, SMT LF - 3-794634-2**

TE INTERNAL NUMBER: 3-794634-2

✓ Active

Always EU RoHS/ELV Compliant

Product Type **Connector**

Mating Alignment **With**

Mating Alignment Type

Polarization

Mating Retention **With**

Mating Retention Type **Locking**

Tab

