



RECTANGULAR POWER CONNECTORS



TE CONNECTIVITY (TE)

2 CIR MINI UMNL RND WIRE HOLES

MATE-N-LOK | Mini-Universal MATE-N-LOK

794896-1

TE Internal Number: 794896-1

Always EU RoHS/ELV Compliant

Product Type **Housing**

Housing Type **Receptacle**

Connector System **Wire-to-Panel, Wire-to-Wire**

Applies To **Panel, Wire/Cable**

Number of Positions **2**

Active

PRODUCT DRAWING
English

3D PDF

Product Drawings

[CAP 2 CIRCUIT SEALED APPLICATION MINI UNIVERSAL MATE N LOK](#)

PDF
English

CAD Files

[3D PDF](#)

PDF
3D

[Customer View Model](#)

2D_DXF.ZIP
English

[Customer View Model](#)

3D_IGS.ZIP
English

[Customer View Model](#)

3D_STP.ZIP
English

Catalog Pages/Data Sheets

[SOFT_SHELL_PIN_AND_SOCKET_CONNECTORS_CATALOG](#)

PDF
English

[1-1773458-0_MINI_UNIVERSAL_MATE_N_LOK_CONNECTOR_SYSTEM_ORG](#)

PDF
English

Product Specifications

Application Specification

[Mini-Universal MATE-N-LOK Splash-Proof Sealed Connectors](#)

PDF
English

Product Environmental Compliance

TE Material Declaration

[MD_794896-1_05052015410_dmtec](#)

PDF
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features	Product Type	Housing
	Housing Type	Receptacle
	Contact Type	Pin

Configuration Features	Number of Positions	2
	Centerline	4.14 mm [.163 in]
	Number of Rows	1
	Contact Layout	Inline
	Multiple Contact Types	Without

Electrical Characteristics	Operating Voltage (VAC)	600
	Operating Voltage (VDC)	600

Contact Features	Contact Retention	Without
------------------	-------------------	----------------

Mechanical Attachment	Panel Mount Retention Type	Mounting Ears
	Panel Mount Retention	With
	Assembly Integration Feature	Without

Housing Features	UL Flammability Rating	UL 94V-0
	Housing Color	Natural
	Housing Material	PA 66/6

Dimensions	Panel Thickness	.8 – 2 mm [.031 – .078 in]
	Length (in)	.983
	Width (in)	.472
	Height (in)	.386

Usage Conditions	Sealed Condition	Not Sealed
------------------	------------------	-------------------





Operation/Application	Connector System	Wire-to-Panel, Wire-to-Wire
	Applies To	Panel, Wire/Cable
	Operating Temperature	-40 – 90 °C [-40 – 194 °F]

Industry Standards	Glow Wire Rating	Standard Part - Not Glow Wire
--------------------	------------------	--------------------------------------

Industry Standards	Glow wire Rating	Standard Part - NOT Glow wire
	VDE Tested	Yes
	Agency/Standard Number	E28476
Packaging Features	Packaging Method	Package
	Packaging Quantity	1
Other	For Use With	Mini-Universal MATE-N-LOK Sealed Plug Housing

Product Compliance [Statement of Compliance PDF](#)
[VIEW ALL PRODUCT COMPLIANCE](#)

CUSTOMERS ALSO BOUGHT

<p>RECTANGULAR CONNECTOR SEALS</p>  <p>02P MINIUMNL GANG WIRE SEAL DR 1586359-2</p> <p>Save to List Find Similar Products</p>	<p>RADIAL-LEADED DEVICES</p>  <p>RHEF750 RHEF750</p> <p>Save to List Find Similar Products</p>	<p>RECTANGULAR CONNECTOR SEALS</p>  <p>02P MINI UMNL SEAL, DIE CUT 794772-2</p> <p>Save to List Find Similar Products</p>	<p>POWER CONTACTS</p>  <p>MINI UMNL PIN 22-18 AWG AU LP 770987-3</p> <p>Save to List Find Similar Products</p>
---	--	---	--

Products - 32 Results

[View All](#)

[Compare 0/10](#)


Relation Type ▼

RELATIONSHIP

Contacts

Identifies Contacts compatible with a given Housing

[See All Contacts](#)

	<p>PRODUCT - CONTACTS</p> <p>Connectors - Power Contacts MATE-N-LOK Mini-Universal MATE-N-LOK</p> <p>MINI UMNL SOK 26-22AWG SN LP - 770986-1</p> <p>TE INTERNAL NUMBER: 770986-1 ALIAS ID: 010-5172-00</p> <p>✓ Active</p>	<p>Always EU RoHS/ELV Compliant</p> <p>Product Type Contact</p> <p>Contact Current Rating 11.2 A</p> <p>Operating Voltage 600 VAC</p> <p>Operating Voltage 600 VDC</p> <p>Wire/Cable Size 26 - 22 AWG</p>	<input checked="" type="checkbox"/>
---	---	--	-------------------------------------

RELATIONSHIP

Contacts

Identifies Contacts compatible with a given Housing

[See All Contacts](#)

PRODUCT - CONTACTS



Connectors - Power Contacts
MATE-N-LOK I Mini-Universal MATE-N-LOK

**MINI UMNL SOK 26-
22AWG AU LP - 770986-3**

TE INTERNAL NUMBER: 770986-3

✓ Active

Not EU RoHS or ELV Compliant

Product Type **Contact**

Contact Current Rating **11.2 A**

Operating Voltage **600 VAC**

Operating Voltage **600 VDC**

Wire/Cable Size **26 – 22 AWG**



RELATIONSHIP

Contacts

Identifies Contacts compatible with a given Housing

[See All Contacts](#)

PRODUCT - CONTACTS



Connectors - Power Contacts
MATE-N-LOK I Mini-Universal MATE-N-LOK

**MINI UMNL SOK 26-22
AWG AU - 770902-3**

TE INTERNAL NUMBER: 770902-3

✓ Active

Not EU RoHS or ELV Compliant

Product Type **Contact**

Contact Current Rating **11.2 A**

Operating Voltage **600 VAC**

Operating Voltage **600 VDC**

Wire/Cable Size **26 – 22 AWG**

