



POWER CONTACTS



TE CONNECTIVITY (TE)

VAL-U-LOK PIN PHBZ SN 18-24AWG

[VAL-U-LOK](#) | [VAL-U-LOK](#)

794955-3

TE Internal Number: 794955-3

Always EU RoHS/ELV Compliant

Product Type **Contact**

Contact Current Rating (A) **9**

Operating Voltage (VAC) **600**

Wire/Cable Size (AWG) **24 – 18**

Wire/Cable Size (mm²) **.2 – .8**

Active

[PRODUCT DRAWING](#)
English

[3D PDF](#)

Product Drawings

[TERMINAL PIN VAL-U-LOK\(TM\)](#)

PDF
English

CAD Files

[Customer View Model](#)

2D_DXF.ZIP
English

[3D PDF](#)

PDF
3D

[Customer View Model](#)

3D_IGS.ZIP
English

[Customer View Model](#)

3D_STP.ZIP
English

Catalog Pages/Data Sheets

[SOFT_SHELL_PIN_AND_SOCKET_CONNECTORS_CATALOG](#)

PDF
English

Product Specifications

Product Specification

[VAL-U-LOK Connectors](#)

PDF
English

Application Specification

[VAL-U-LOK Series Headers, Connectors And TPA Accessories](#)

PDF
English

Qualification Test Report

[VAL-U-LOK Connectors](#)

PDF
English

Product Environmental Compliance

TE Material Declaration

[MD_794955-3_04012015339_dmtec](#)

PDF
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.





Product Type Features	Product Type	Contact
Electrical Characteristics	Contact Current Rating (A)	9
	Operating Voltage (VAC)	600
Contact Features	Contact Type	Pin
	Contact Base Material	Phosphor Bronze
	Contact Mating Area Plating Material	Pre-Tin
	Contact Mating Area Plating Thickness	2.54 μm [100 μin]
	Contact Design	Formed Pin
Termination Features	Wire/Cable Size (AWG)	24 – 18
	Wire/Cable Size (mm ²)	.2 – .8
	Termination Type	Crimp
Dimensions	Accepts Wire Insulation Diameter Range	1.5 – 3.1 mm [.059 – .122 in]
Operation/Application	Circuit Application	Signal
	Operating Temperature Range	-40 – 105 °C [-40 – 221 °F]
	Connector System	Wire-to-Wire
Industry Standards	Glow Wire Rating	Standard Part - Not Glow Wire
	UL File Number	E28476
	Agency/Standard	CSA, UL
	CSA File Number	208567
	UL Rating	Recognized
Packaging Features	Packaging Method	Reel
	Packaging Quantity	3500
Other	Wire/Cable Type	Discrete Wire

Product Compliance

[Statement of Compliance](#)
PDF

[VIEW ALL PRODUCT COMPLIANCE](#)

CUSTOMERS ALSO BOUGHT

<p>RECTANGULAR POWER CONNECTORS</p>  <p>16P FH PLUG VAL-U-LOK V2 1-1586000-6</p> <p>Save to List Find Similar Products</p>	<p>RECTANGULAR POWER CONNECTORS</p>  <p>4P PM PLUG VAL-U-LOK V2 794953-4</p> <p>Save to List Find Similar Products</p>	<p>PRO-CRIMPER & DIES</p>  <p>PRO-CRIMPER TOOL & DIE 91388-1</p> <p>Save to List Find Similar Products</p>	<p>POWER CONTACTS</p>  <p>VAL-U-LOK SKT PHBZ SN 24-18 LP 1586315-3</p> <p>Save to List Find Similar Products</p>
-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Products - 5 Results

[View All](#)

[Compare 0/10](#)

Relation Type ▼

RELATIONSHIP

Toolings

Tooling

[See All Toolings](#)

PRODUCT - TOOLINGS



Application Tooling - OCEAN Applicators
AMP

OC-PA-S-FA-062F125F-001-0296 - 2-2151096-2
TE INTERNAL NUMBER: 2-2151096-2

✓ Active

Not in Scope for EU RoHS/ELV
Compliance

Region **Worldwide**

Tool Type **Applicator**

Spare Parts Tooling **No**

Applicator Style **OCEAN - Pacific**

Applicator Feed Style **Side Feed**



RELATIONSHIP

Toolings

Tooling

[See All Toolings](#)

PRODUCT - TOOLINGS



Application Tooling - OCEAN Applicators
AMP

OC-AT-S-FM-062F125F-001-0296 - 2151096-1
TE INTERNAL NUMBER: 2151096-1

✓ Active

Not in Scope for EU RoHS/ELV
Compliance

Region **Worldwide**

Tool Type **Applicator**

Spare Parts Tooling **No**

Applicator Style **OCEAN -**



Atlantic

Applicator Feed Style **Side Feed**

RELATIONSHIP

Toolings

Tooling

[See All Toolings](#)

PRODUCT - TOOLINGS



Application Tooling - OCEAN Applicators
AMP

OC-062F125F- CRIMPTOOLINGKIT - 7-2151096-7

TE INTERNAL NUMBER: 7-2151096-7

✓ Active

Not in Scope for EU RoHS/ELV
Compliance

Region **Worldwide**

Tool Type **Applicator**

Spare Parts Tooling **Yes**

Spare Parts Tool Type **Spare**

Parts Kit

