



POWER CONTACTS



TE CONNECTIVITY (TE)

VAL-U-LOK PIN BR SN 22-26AWG

[VAL-U-LOK](#) | [VAL-U-LOK](#)

794957-1

TE Internal Number: 794957-1

Always EU RoHS/ELV Compliant

Product Type **Contact**

Contact Current Rating (A) **9**

Operating Voltage (VDC) **250**

Wire/Cable Size (AWG) **26 – 22**

Wire/Cable Size (mm²) **.13 – .32**

Active

[PRODUCT DRAWING](#)
English

[3D PDF](#)

Product Drawings

[TERMINAL PIN VAL-U-LOK\(TM\)](#)

PDF
English

CAD Files

[Customer View Model](#)

2D_DXF.ZIP
English

[3D PDF](#)

PDF
3D

[Customer View Model](#)

3D_IGS.ZIP
English

[Customer View Model](#)

3D_STP.ZIP
English

Catalog Pages/Data Sheets

[SOFT_SHELL_PIN_AND_SOCKET_CONNECTORS_CATALOG](#)

PDF
English

Product Specifications

Product Specification

[VAL-U-LOK Connectors](#)

PDF
English

Application Specification

[VAL-U-LOK Series Headers, Connectors And TPA Accessories](#)

PDF
English











Qualification Test Report

[VAL-U-LOK Connectors](#)

PDF
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features	Product Type	Contact
Electrical Characteristics	Contact Current Rating (A)	9
	Operating Voltage (VDC)	250
Contact Features	Contact Type	Pin
	Contact Base Material	Brass
	Contact Mating Area Plating Material	Pre-Tin
	Contact Mating Area Plating Thickness	2.54 µm [100 µin]
	Contact Design	Formed Pin
Termination Features	Wire/Cable Size (AWG)	26 – 22
	Wire/Cable Size (mm ²)	.13 – .32
	Termination Type	Crimp
Dimensions	Accepts Wire Insulation Diameter Range	1.2 – 1.75 mm [.047 – .069 in]
Operation/Application	Circuit Application	Signal
	Operating Temperature Range	-40 – 105 °C [-40 – 221 °F]
	Connector System	Wire-to-Wire
Industry Standards	Glow Wire Rating	Standard Part - Not Glow Wire
	UL File Number	E28476
	Agency/Standard	CSA, UL
	CSA File Number	208567
	UL Rating	Recognized
Packaging Features	Packaging Method	Reel
	Packaging Quantity	5000
Other	Wire/Cable Type	Discrete Wire
Product Compliance	Statement of Compliance PDF VIEW ALL PRODUCT COMPLIANCE	

RECTANGULAR POWER CONNECTORS	POWER CONTACTS	POWER CONTACTS	RECTANGULAR POWER CONNECTORS
			
<p>2P FH PLUG VAL-U-LOK V2 1586000-2</p>	<p>VAL-U-LOK SKT PHBZ SN 26-22 LP 1586317-3</p>	<p>VAL-U-LOK SKT BR SN 22- 26AWG 794958-1</p>	<p>6P FH PLUG VAL-U-LOK V2 1586000-6</p>
<p> Save to List  Find Similar Products</p>	<p> Save to List  Find Similar Products</p>	<p> Save to List  Find Similar Products</p>	<p> Save to List  Find Similar Products</p>