




RIBBON CABLE CONNECTORS



Active

PRODUCT DRAWING
English

3D PDF

TE CONNECTIVITY (TE)

MICRO-MATCH SMD FTE

Micro-MaTch | Micro-MaTch Industrial

8-338069-0

TE Internal Number: 8-338069-0

Always EU RoHS/ELV Compliant

Centerline **1.27 mm [.05 in]**

PCB Mount Retention **Without**

PCB Mounting Orientation **Vertical**

Termination Method to PC Board **Surface Mount**

Shrouded **Yes**

Product Drawings

[CONNECTOR, FEMALE-ON-BOARD TOP-ENTRY, SMD, WITH LATCHES, Micro-MaTch](#)

PDF
English

CAD Files

[3D PDF](#)

PDF
English

[Customer View Model](#)

2D_DXF.ZIP
English

[Customer View Model](#)

3D_IGS.ZIP
English

[Customer View Model](#)

3D_STP.ZIP
English

Catalog Pages/Data Sheets

[Micro-MaTch Catalog](#)

PDF
English

[Centerline Micro-Match Connector Series](#)

PDF
English

Product Specifications

Product Specification

[Amp Micro-Match Miniature Connector Assembly](#)

PDF
English

Application Specification

[Micro-MaTch Miniature Surface Mounting Device \(SMD\) Printed Circuit \(PC\) Board Connectors](#)

PDF
English

Qualification Test Report

[Test Report Lead-Free Reflow Soldering-Heat \(SMD Connectors\)](#)

PDF
English

Product Environmental Compliance

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features	PCB Mounting Orientation	Vertical
	Shrouded	Yes
	Connector Style	Receptacle
	Profile	Standard
	Applies To	Printed Circuit Board
	Product Type	Connector
	Board Standoff	Without
	Connector Type	Connector Assembly
	Type of Connector	Female-on-Board
	Connector System	Board-to-Board
Ejection Latches	Without	

Configuration Features	Number of Positions	10
------------------------	---------------------	-----------

Electrical Characteristics	Insulation Resistance (MΩ)	1000
	Operating Voltage (VDC)	100

Body Features	Header Type	Pin Header
	Daisy Chain	Without

Contact Features	Contact Mating Area Plating Material	Tin over Nickel
	Contact Design	Dual Beam
	Vacuum Tape	With
	Contact Transmits (Typical)	Signal (Data)
	Solder Tail Contact Plating Material	Tin over Nickel
	Contact Current Rating (A)	1.4
	Contact Base Material	Copper Alloy
	Contact Type	Socket
	Contact Termination Area Plating Material	Tin over Nickel

Termination Features	Termination Method to PC Board	Surface Mount
----------------------	--------------------------------	----------------------

Termination Post Length **5.3 mm [.208 in]**

Mechanical Attachment	PCB Mount Retention	Without
	Mating Alignment Type	Polarization
	Mating Connector Lock	With
	Mating Retention Type	Locking Latch
	Mating Alignment	Without
	Polarization	With
	Panel Mount Retention	Without
	Mating Retention	Without
	PCB Mount Alignment	Without

Housing Features	Centerline	1.27 mm [.05 in]
	Housing Color	Black
	Housing Entry Style	Top
	Housing Material	PA 4.6

Dimensions	Height	6.9 mm [.27 in]
	Length	17.3 mm [.681 in]
	PCB Thickness (Recommended)	1.6 mm [.062 in]

Usage Conditions	Operating Temperature Range (°C)	-30 – 85
------------------	----------------------------------	-----------------

Industry Standards	UL Flammability Rating	UL 94V-0
--------------------	------------------------	-----------------

Packaging Features	Packaging Method	Reel
	Packaging Quantity	900

Product Compliance [Statement of Compliance](#)
PDF

[VIEW ALL PRODUCT COMPLIANCE](#)

CUSTOMERS ALSO BOUGHT

RJ45 CONNECTORS 		SURFACE MOUNT RESISTORS 	RIBBON CABLE CONNECTORS 
---	---	---	---

8/8 PCB MOD.JACK BE 188728-1	RYA50012 2-1393224-4	RL73K 3A R33 5% 4K RL RL73K3AR33JTE	MICRO-MATCH SMD FTE 338069-8
Save to List Find Similar Products	Save to List Find Similar Products	Save to List Find Similar Products	Save to List Find Similar Products

Products - 8 Results

[View All](#)

Compare 0/10

Relation Type

RELATIONSHIP

Mating Products

Used to identify Mating Parts

[See All Mating Products](#)

PRODUCT - MATING PRODUCTS



Connectors - Ribbon Cable Connectors
Micro-MaTch I Micro-MaTch Industrial

10P.MICRO-MATCH
MOB - 1-215464-0

TE INTERNAL NUMBER: 1-215464-0

Active

Always EU RoHS/ELV Compliant

Centerline **1.27 mm**

PCB Mount Retention **With**

PCB Mount Retention Type **Kink**

PCB Mounting Orientation

Vertical

Termination Method to PC Board

Through Hole



RELATIONSHIP

Mating Products

Used to identify Mating Parts

[See All Mating Products](#)

PRODUCT - MATING PRODUCTS



Connectors - Ribbon Cable Connectors
Micro-MaTch I Micro-MaTch Industrial

MICROM. MOB SMD
CON - 1-338728-0

TE INTERNAL NUMBER: 1-338728-0

Active

Always EU RoHS/ELV Compliant

Centerline **1.27 mm**

PCB Mount Retention **Without**

PCB Mounting Orientation

Vertical

Termination Method to PC Board

Surface Mount

Shrouded **Yes**



RELATIONSHIP

Mating Products

Used to identify Mating Parts

[See All Mating Products](#)

PRODUCT - MATING PRODUCTS





Connectors - Ribbon Cable Connectors
Micro-MaTch I Micro-MaTch Industrial

MICRO-MATCH

MOW.10P - 1-215083-0

TE INTERNAL NUMBER: 1-215083-0

✓ Active

Always EU RoHS/ELV Compliant

Centerline **1.27 mm**

PCB Mount Retention **Without**

PCB Mounting Orientation

Vertical

Termination Method to

Wire/Cable **Insulation**

Displacement Crimp (IDC)

Shrouded **Yes**

