




# MULTIPLE CONFIGURATION PCB HEADERS & RECEPTACLES



Active

PRODUCT DRAWING  
English

3D PDF

## TE CONNECTIVITY (TE) 2P AMPMODU II AMPMODU | AMPMODU Headers

826629-2  
TE Internal Number: 826629-2

Always EU RoHS/ELV Compliant  
Applies To **Printed Circuit Board**

Connector Style **Plug**  
Centerline **2.54 mm [ .1 in ]**

Number of Positions **2**  
Header Type **Unshrouded**

### Product Drawings

[AMPMODU II STIFTLISTEN 90 DEG. ,EINREIHIG](#)  
PDF  
English

### CAD Files

[Customer View Model](#)  
2D\_DXF.ZIP  
English

[Customer View Model](#)  
3D\_IGS.ZIP  
English

[Customer View Model](#)  
3D\_STP.ZIP  
English

[3D PDF](#)  
PDF  
English

### Product Environmental Compliance

TE Material Declaration [MD\\_826629-2\\_060520142344\\_dmtec](#)  
PDF  
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

### Product Type Features

Applies To	<b>Printed Circuit Board</b>
Connector Style	<b>Plug</b>
PCB Mounting Orientation	<b>Vertical</b>
Connector Type	<b>Header</b>

	Row-to-Row Spacing	<b>2.54 mm [ .1 in ]</b>
	Stabilizers	<b>Without</b>
	Strain Relief	<b>Without</b>
	Board Standoff	<b>Without</b>
	Profile	<b>Standard</b>
	Product Type	<b>Connector</b>
	Gasket	<b>Without</b>
<hr/>		
Configuration Features	Number of Positions	<b>2</b>
	Number of Rows	<b>1</b>
	Keyed	<b>No</b>
	Selectively Loaded	<b>No</b>
<hr/>		
Body Features	Header Type	<b>Unshrouded</b>
	Post Size	<b>.63 mm [ .024 in ]</b>
<hr/>		
Contact Features	Contact Protection	<b>Without</b>
	Contact Shape	<b>Square</b>
	Contact Type	<b>Pin</b>
	Contact Base Material	<b>Phosphor Bronze</b>
	Solder Tail Contact Plating Material	<b>Tin</b>
	Contact Mating Area Plating Thickness (µm)	<b>.8</b>
	Contact Mating Area Plating Material	<b>Gold</b>
<hr/>		
Termination Features	Termination Post Length	<b>3.2 mm [ .1259 in ]</b>
	Termination End Plating Material	<b>Tin Over Nickel</b>
	Termination End Plating Thickness (µm)	<b>3</b>
	Termination Method to PC Board	<b>Through Hole</b>
<hr/>		
Mechanical Attachment	PCB Mounting Style	<b>Straddle Mount</b>
	PCB Mount Retention	<b>Without</b>
	Panel Mount Retention	<b>Without</b>
	Mating Alignment	<b>Without</b>
	Mating Connector Lock	<b>Without</b>
<hr/>		
Housing Features	Centerline	<b>2.54 mm [ .1 in ]</b>

Housing Color **Green**

Housing Material **PBT GV**

Dimensions Mating Post Length **6.7 mm [ .264 in ]**

Usage Conditions High Temperature Housing **No**

Operation/Application High Speed Serial Data Connector **No**

Industry Standards UL Flammability Rating **UL 94V-0**





Packaging Features Packaging Quantity **3000**

Packaging Method **Carton**

Product Compliance [Statement of Compliance](#)  
PDF

[VIEW ALL PRODUCT COMPLIANCE](#)

## CUSTOMERS ALSO BOUGHT

RIBBON CABLE CONNECTORS	MULTIPLE CONFIGURATION PCB HEADERS & RECEPTACLES	AUTOMOTIVE, TRUCK, BUS, & OFF-ROAD TERMINALS	MULTIPLE CONFIGURATION PCB HEADERS & RECEPTACLES
 <p>034 LOPRO HDR SP 15DP 103308-7</p>	 <p>16 MODII HDR DRST SFMNT B/A LF 5-146130-7</p>	 <p>TAB 1, 2 ( 0, 5-0, 75MM) 5-1418760-1</p>	 <p>4P AMPMODU II PIN HSG 826629-4</p>
<a href="#">Save to List</a> <a href="#">Find Similar Products</a>	<a href="#">Save to List</a> <a href="#">Find Similar Products</a>	<a href="#">Save to List</a> <a href="#">Find Similar Products</a>	<a href="#">Save to List</a> <a href="#">Find Similar Products</a>