



MULTIPLE CONFIGURATION PCB HEADERS & RECEPTACLES



Active

PRODUCT DRAWING
English

3D PDF

TE CONNECTIVITY (TE) 3P AMPMODU II STIFT LEI

AMPMODU | AMPMODU Headers

826631-3

TE Internal Number: 826631-3

Always EU RoHS/ELV Compliant

Applies To **Printed Circuit Board**

Connector Style **Plug**

Centerline **2.54 mm [.1 in]**

Number of Positions **3**

Header Type **Breakaway**

Product Drawings

[AMPMODU II STIFTLISTE 90DEG EINREIHIG](#)

PDF
English

CAD Files

[3D PDF](#)

PDF
3D

[Customer View Model](#)

2D_DXF.ZIP
English

[Customer View Model](#)

3D_IGS.ZIP
English

[Customer View Model](#)

3D_STP.ZIP
English

Product Environmental Compliance

TE Material Declaration

[MD_826631-3_01092015843_dmtec](#)

PDF
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features

Applies To

Printed Circuit Board

Connector Style

Plug

PCB Mounting Orientation

Right Angle

Connector Type

Header

Row-to-Row Spacing	2.54 mm [.1 in]
Stabilizers	Without
Strain Relief	Without
Board Standoff	Without
Profile	Standard
Product Type	Connector
Gasket	Without

Configuration Features	Number of Positions	3
	Number of Rows	1
	Keyed	No
	Selectively Loaded	No

Body Features	Header Type	Breakaway
	Post Size (mm)	.63

Contact Features	Contact Protection	Without
	Contact Type	Pin
	Contact Base Material	Phosphor Bronze
	Contact Mating Area Plating Thickness (µin)	30
	Solder Tail Contact Plating Material	Tin
	Contact Mating Area Plating Material	Gold


Termination Features	Termination Post Length	3.2 mm [.1259 in]
	Termination End Plating Material	Tin Over Nickel
	Termination End Plating Thickness (µm)	3
	Termination Method to PC Board	Through Hole

Mechanical Attachment	PCB Mount Retention	Without
	Panel Mount Retention	Without
	Mating Alignment	Without
	Mating Connector Lock	Without

Housing Features	Centerline	2.54 mm [.1 in]
	Housing Color	Green
	Housing Material	Thermoplastic

Dimensions	PCB Thickness (Recommended) (in)	.062
	Mating Post Length	6.7 mm [.264 in]
Usage Conditions	High Temperature Housing	No
Operation/Application	High Speed Serial Data Connector	No
Industry Standards	UL Flammability Rating	UL 94V-0
	Approved Standards	CSA LR7189, CUL E28476
Packaging Features	Packaging Quantity	1500
	Packaging Method	Box
Product Compliance	Statement of Compliance PDF VIEW ALL PRODUCT COMPLIANCE	


CUSTOMERS ALSO BOUGHT



**RP 1J 0.166W 200K 0.1%
25PPM 1K RL
RP73PF1J200KBTDF**

[Save to List](#)
[Find Similar Products](#)


PCB D-SUB CONNECTORS



**HD-20 PLUG 37P RA 590
5747470-2**

[Save to List](#)
[Find Similar Products](#)


AUTOMOTIVE, TRUCK, BUS, &
OFF-ROAD HEADERS



**MESSERLEISTE 15P
966140-2**

[Save to List](#)
[Find Similar Products](#)

PCB D-SUB CONNECTORS



**AMP III PLUG 25P RA 590
THD IN
5748873-1**

[Save to List](#)
[Find Similar Products](#)