




MULTIPLE CONFIGURATION PCB HEADERS & RECEPTACLES



✓ Active

↓ **PRODUCT DRAWING**
English

TE CONNECTIVITY (TE) 3P AMPMODU II STIFT LEI

AMPMODU | AMPMODU Headers

826936-3

TE Internal Number: 826936-3

Always EU RoHS/ELV Compliant

Applies To **Printed Circuit Board**

Connector Style **Plug**

Centerline **2.54 mm [.1 in]**

Number of Positions **3**

Header Type **Breakaway**

Product Drawings

[AMPMODU II BREAK AWAY HEADER, SGL ROW, TIN PLATE B5.8](#)

PDF
English

[AMPMODU II STIFTLISTEN 90 DEG. ,EINREIHIG](#)

PDF
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features

Applies To	Printed Circuit Board
Connector Style	Plug
PCB Mounting Orientation	Vertical
Connector Type	Header
Row-to-Row Spacing	2.54 mm [.1 in]
Stabilizers	Without
Strain Relief	Without
Board Standoff	Without
Profile	Standard
Product Type	Connector
Gasket	Without





Configuration Features

Number of Positions	3
Number of Rows	1

	Number of Rows	1
	Keyed	No
	Selectively Loaded	No
Electrical Characteristics	Dielectric Withstanding Voltage	1000 V
Body Features	Header Type	Breakaway
	Post Size	.63 mm [.024 in]
Contact Features	Contact Protection	Without
	Contact Shape	Square
	Contact Type	Pin
	Contact Base Material	Phosphor Bronze
	Solder Tail Contact Plating Material	Tin
	Contact Mating Area Plating Thickness (µm)	2
	Contact Mating Area Plating Material	Tin
	Contact Current Rating (A)	5
Termination Features	Termination Post Length	3.2 mm [.1259 in]
	Termination End Plating Material	Tin
	Termination End Plating Thickness (µm)	2
	Termination Method to PC Board	Through Hole
Mechanical Attachment	PCB Mounting Style	Through Hole
	PCB Mount Retention	Without
	Panel Mount Retention	Without
	Mating Alignment	Without
	Mating Connector Lock	Without
Housing Features	Centerline	2.54 mm [.1 in]
	Housing Color	Green
	Housing Material	PBT GV
Dimensions	Mating Post Length	5.8 mm [.228 in]
Usage Conditions	Operating Temperature Range (°C)	-65 – 105
	High Temperature Housing	No

Operation/Application	High Speed Serial Data Connector	No
Industry Standards	UL Flammability Rating	UL 94V-0
Packaging Features	Packaging Quantity	1500
	Packaging Method	Carton
Product Compliance	Statement of Compliance PDF VIEW ALL PRODUCT COMPLIANCE	

CUSTOMERS ALSO BOUGHT

<p>MULTIPLE CONFIGURATION PCB HEADERS & RECEPTACLES</p>  <p>2P AMPMODU II STIFT LEI 826936-2</p> <p>Save to List Find Similar Products</p>	<p>MULTIPLE CONFIGURATION PCB HEADERS & RECEPTACLES</p>  <p>16P AMPMODU II STIFT LEI 1-826936-6</p> <p>Save to List Find Similar Products</p>	<p>SURFACE MOUNT RESISTORS</p>  <p>CPF 0402 27K 0.1% 25PPM 1K RL CPF0402B27KE1</p> <p>Save to List Find Similar Products</p>	<p>SURFACE MOUNT RESISTORS</p>  <p>CPF 0603 270R 0.1% 25PPM 1K RL CPF0603B270RE1</p> <p>Save to List Find Similar Products</p>
--	---	---	---