



## BOARD-TO-BOARD JUMPERS & SHUNTS



Active

PRODUCT DRAWING  
English

3D PDF

TE CONNECTIVITY (TE)

### SHUNT LP W/HANDLE 2 POS 30AU

AMP | PKS

881545-2

TE Internal Number: 881545-2

Alias ID: 407120377

Always EU RoHS/ELV Compliant

Shunt Type **Novo**

Shunt Style **Open Top**

Centerline **2.54 mm [ .1 in ]**

Number of Positions **2**

#### Product Drawings

[Shunt Low Profile Connector Assy](#)

PDF  
English

#### CAD Files

[3D PDF](#)

PDF  
English

[Customer View Model](#)

2D\_DXF.ZIP  
English

[Customer View Model](#)

3D\_IGS.ZIP  
English

[Customer View Model](#)

3D\_STP.ZIP  
English

#### Catalog Pages/Data Sheets

[AMPMODU\\_INTERCONNECTION\\_SYSTEM\\_SECTION\\_6\\_7AND8](#)

PDF  
English

#### Product Environmental Compliance

TE Material Declaration

[MD\\_881545-2\\_070720142324\\_dmtec](#)

PDF  
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features

Profile

**Low**

Product Type


**Shunt**

Configuration Features	Number of Positions	<b>2</b>
Electrical Characteristics	Termination Resistance (mΩ)	<b>15</b>
Body Features	Handle	<b>With</b>
Contact Features	Shunt Type	<b>Novo</b>
	Shunt Style	<b>Open Top</b>
	Contact Current Rating (A)	<b>3</b>
	Contact Base Material	<b>Phosphor Bronze</b>
	Contact Mating Area Plating Thickness	<b>.762 μm [ 30 μin ]</b>
	Contact Mating Area Plating Material	<b>Gold</b>
Housing Features	Centerline	<b>2.54 mm [ .1 in ]</b>
	Housing Material	<b>Thermoplastic</b>
	Housing Color	<b>Black</b>
Dimensions	Height	<b>10.9 mm [ .429 in ]</b>
Usage Conditions	Operating Temperature Range (°C)	<b>-65 – 105</b>
Industry Standards	UL Flammability Rating	<b>UL 94V-0</b>
Packaging Features	Packaging Method	<b>Bag</b>
	Packaging Quantity	<b>14000</b>
Product Compliance	<a href="#">Statement of Compliance</a> PDF <a href="#">VIEW ALL PRODUCT COMPLIANCE</a>	


## CUSTOMERS ALSO BOUGHT

<p><b>SURFACE MOUNT RESISTORS</b></p>  <p><b>CPF 0603 158K 0.1% 25PPM 1K RL</b>  <a href="#">1-5102159-0</a></p>	<p><b>RIBBON CABLE CONNECTORS</b></p>  <p><b>A/L UNIV HDR 50P RA</b>  <a href="#">1-5102159-0</a></p>	 <p><b>RP 2A 0.25W 64K9 0.1% 25PPM 1K RL</b>  <a href="#">7-2176093-7</a></p>	<p><b>PLUGGABLE I/O CABLE ASSEMBLIES</b></p>  <p><b>C/A, QSFP TO 4XSFP+, 1.0M</b></p>
---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	----------------------------------------------------------------------------------------------------------------------------------------------------------------------	----------------------------------------------------------------------------------------------------------------------------------------------------------------------------

CPF0603B158KE1

 Save to List

 Find Similar Products

 Save to List

 Find Similar Products

2053453-2

 Save to List

 Find Similar Products

 Save to List

 Find Similar Products

