




# MULTIPLE CONFIGURATION PCB HEADERS & RECEPTACLES



Active

PRODUCT DRAWING  
English

3D PDF

TE CONNECTIVITY (TE)

## 80 MODII HDR DRRA B/A .100CL

AMPMODU | AMPMODU Headers

9-102975-0

TE Internal Number: 9-102975-0

Always EU RoHS/ELV Compliant

Applies To **Printed Circuit Board**

Connector Style **Plug**

Centerline **2.54 mm [ .1 in ]**

Number of Positions **80**

Header Type **Breakaway**

### Product Drawings

[HEADER ASSY, MOD II, BREAKAWAY, DOUBLE ROW, .100X.100 CL, RIGHT ANGLE WITH .025 SQ POSTS](#)

PDF  
English

### CAD Files

[Customer View Model](#)

2D\_DXF.ZIP  
English

[3D PDF](#)

PDF  
English

[Customer View Model](#)

3D\_IGS.ZIP  
English

[Customer View Model](#)

3D\_STP.ZIP  
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

### Product Type Features

Applies To

**Printed Circuit Board**

Connector Style

**Plug**

PCB Mounting Orientation

**Right Angle**

Connector Type

**Header**

Row-to-Row Spacing

**2.54 mm [ .1 in ]**

Stabilizers

**Without**

Strain Relief

**Without**

	Strain Relief	<b>Without</b>
	Board Standoff	<b>Without</b>
	Product Type	<b>Connector</b>
	Gasket	<b>Without</b>
<hr/>		
Configuration Features	Number of Positions	<b>80</b>
	Number of Rows	<b>2</b>
	Keyed	<b>No</b>
	Selectively Loaded	<b>No</b>
<hr/>		
Electrical Characteristics	Dielectric Withstanding Voltage	<b>750 V</b>
<hr/>		
Body Features	Header Type	<b>Breakaway</b>
	Post Size	<b>.64 mm [ .025 in ]</b>
<hr/>		
Contact Features	Contact Protection	<b>Without</b>
	Contact Shape	<b>Square</b>
	Contact Type	<b>Pin</b>
	Contact Base Material	<b>Copper Alloy</b>
	Contact Mating Area Plating Thickness (µin)	<b>15</b>
	Solder Tail Contact Plating Material	<b>Tin over Nickel</b>
	Contact Mating Area Plating Material	<b>Gold</b>
	Contact Current Rating (A)	<b>3</b>
<hr/>		
Termination Features	Termination Post Length	<b>2.79 mm [ .11 in ]</b>
	Termination End Plating Thickness (µin)	<b>100 – 200</b>
	Termination End Plating Material	<b>Tin Over Nickel</b>
	Termination Method to PC Board	<b>Through Hole</b>
<hr/>		
Mechanical Attachment	PCB Mounting Style	<b>Through Hole</b>
	PCB Mount Retention	<b>Without</b>
	Panel Mount Retention	<b>Without</b>
	Mating Alignment	<b>Without</b>
	Mating Connector Lock	<b>Without</b>
<hr/>		
Housing Features	Centerline	<b>2.54 mm [ .1 in ]</b>
	Housing Color	<b>Black</b>





	Housing Material	<b>Thermoplastic</b>
Dimensions	Mating Post Length	<b>8.08 mm [ .318 in ]</b>
Usage Conditions	Operating Temperature Range (°C)	<b>-65 – 105</b>
	High Temperature Housing	<b>No</b>
Operation/Application	High Speed Serial Data Connector	<b>No</b>
Industry Standards	UL Flammability Rating	<b>UL 94V-0</b>
	Approved Standards	<b>CSA LR7189, UL E28476</b>
Packaging Features	Packaging Quantity	<b>50</b>
	Packaging Method	<b>Carton</b>
Other	Comment	<b>Headers may be broken to desired number of positions using Hand Tool No. 91406-1, or Tool Kit No. 314818-1. Other tail lengths are available, consult TE Connectivity.</b>

Product Compliance

[Statement of Compliance](#)  
PDF

[VIEW ALL PRODUCT COMPLIANCE](#)

## CUSTOMERS ALSO BOUGHT

<p><b>BOARD-TO-BOARD HEADERS &amp; RECEPTACLES</b></p>  <p><b>06 MODII HORZ DR CE EESS .100</b> 6-5535512-2</p> <p><a href="#">Save to List</a> <a href="#">Find Similar Products</a></p>	<p><b>MULTIPLE CONFIGURATION PCB HEADERS &amp; RECEPTACLES</b></p>  <p><b>10 MODII HDR SRRA UNSHRD .100</b> 1-87233-0</p> <p><a href="#">Save to List</a> <a href="#">Find Similar Products</a></p>	<p><b>BOARD-TO-BOARD HEADERS &amp; RECEPTACLES</b></p>  <p><b>36 MODIV VRT DR CE 100/125</b> 1-534998-8</p> <p><a href="#">Save to List</a> <a href="#">Find Similar Products</a></p>	<p><b>MULTIPLE CONFIGURATION PCB HEADERS &amp; RECEPTACLES</b></p>  <p><b>80 MODII HDR DRRA B/A .100CL</b> 9-146309-0</p> <p><a href="#">Save to List</a> <a href="#">Find Similar Products</a></p>
--	--	--	--