




## 925590-1 Product Details



**925590-1**

TE Internal Number: 925590-1

**Active**

### Timer Contacts

Always EU RoHS/ELV Compliant (Statement of Compliance)

#### Product Highlights:

- Timer Products Product Line
- Junior Timer Series
- Wire-to-Wire
- Applies To Wire/Cable
- Contact

[View all Features](#)

### Quick Links

- ▶ [Pricing & Availability](#)
- ▶ [Search for Tooling](#)
- ▶ [Product Feature Selector](#)
- ▶ [Contact Us About This Product](#)

[Add to My Part List](#) | 
 [Request Sample](#) | 
 [Find Similar Products](#) | 
 [Buy Product](#)

### Documentation & Additional Information

Documents are temporarily unavailable. We are working hard to correct the problem. Please try again later.

#### Additional Information:

- [Product Line Information](#)

#### Additional Product Images:

- [Line Drawing](#)

#### Related Products:

- [Tooling](#)

### Product Features (Please use the Product Drawing for all design activity)

#### Product Type Features:

- Product Line = Timer Products
- Product Type = Contact
- Cable Type = FLK (Vehicle Cable Plastic)
- Wire/Cable Type = Discrete Wire

#### Electrical Characteristics:

- Contact - Rated Current (A) = 20

#### Termination Features:

- Wire/Cable Size (AWG) = 15 - 20
- Wire/Cable Size (mm<sup>2</sup>) = 0.5 - 1.5
- Termination Method to Wire/Cable = Crimp

#### Dimensions:

- Mating Area Interface Dimensions (mm [in]) = 2.79 x 0.79 [.110 x .031], 3.00 x 0.80 [.118 x .031]

#### Contact Features:

- Contact Type = Socket
- Contact Design = Standard Flat
- Contact Base Material = CuZn30
- Contact Plating, Mating Area, Material = Pre-Tin

#### Configuration Features:

- GET 0.64 Connector System = No
- Single Wire Sealing System = No

#### Industry Standards:

- [RoHS/ELV Compliance](#) = RoHS compliant, ELV compliant
- [Lead Free Solder Processes](#) = Not relevant for lead free process
- RoHS/ELV Compliance History = Always was RoHS compliant
- Agency/Standard = IEC 664/664A (DIN VDE 0110)

#### Environmental:

- Operating Temperature (°C [°F]) = -40 - +110 [-40 - +230]

#### Conditions for Usage:

- Applies To = Wire/Cable
- Accepts Wire Insulation Diameter, Range (mm [in]) = 2.00 - 3.00 [0.079 - 0.118]

#### Operation/Application:

- Application Use = Wire-to-Wire
- Contact Transmits (Typical Application) = Power

#### Packaging Features:

- Packaging Method = Reel
- Packaging Quantity = 4,000

#### Other:

- Series = Junior Timer
- Brand = AMP

Feedback

### Corporate Information

- [About TE](#)
- [Investors](#)
- [News Room](#)
- [Supplier Portal](#)
- [Careers](#)
- [Terms & Conditions](#)
- [Privacy Policy](#)
- [AODA Accessibility Policy](#)

### Quick Links

- [Distributor Inventory](#)
- [Product Cross Reference](#)
- [Documents & Drawings](#)
- [Product Compliance Support Center](#)
- [Site Map](#)

### Customer Support

- [Email or Chat With Us](#)
- [Find a Phone Number](#)
- [Knowledge Base](#)
- [Manage Your Account](#)

### Keep Me Informed



