



# RECTANGULAR POWER CONNECTORS



**TE CONNECTIVITY (TE)**  
**8P UN-MNL STECKGEH**  
[MATE-N-LOK](#) | [Universal MATE-N-LOK](#)

926301-3  
 TE Internal Number: 926301-3

Always EU RoHS/ELV Compliant

Product Type **Housing**

Housing Type **Plug**

Connector System **Wire-to-Wire**

Applies To **Wire/Cable**

Number of Positions **8**

Active

[PRODUCT DRAWING](#)  
English

[3D PDF](#)

## Product Drawings

[Universal Mate N Lok 8 Polig](#)

PDF  
English

## CAD Files

[Customer View Model](#)

2D\_DXF.ZIP  
English

[3D PDF](#)

PDF  
3D

[Customer View Model](#)

3D\_IGS.ZIP  
English

[Customer View Model](#)

3D\_STP.ZIP  
English

## Product Specifications

Product Specification

[Universal MATE-N-LOK Connector](#)

PDF  
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

## Product Type Features

Product Type

**Housing**

Housing Type

**Plug**

Contact Type

**Pin or Socket**

## Configuration Features

Number of Positions

**8**













	Centerline	<b>6.35 mm [ .25 in ]</b>
	Number of Rows	<b>1</b>
	Contact Layout	<b>Inline</b>
	Multiple Contact Types	<b>Without</b>
Electrical Characteristics	Operating Voltage (VAC)	<b>600</b>
	Operating Voltage (VDC)	<b>600</b>
Contact Features	Contact Retention	<b>Without</b>
Mechanical Attachment	Panel Mount Retention	<b>Without</b>
	Assembly Integration Feature	<b>Without</b>
Housing Features	UL Flammability Rating	<b>UL 94V-0</b>
	Housing Color	<b>White</b>
	Housing Material	<b>Nylon</b>
Usage Conditions	Sealed Condition	<b>Not Sealed</b>
Operation/Application	Connector System	<b>Wire-to-Wire</b>
	Applies To	<b>Wire/Cable</b>
	Operating Temperature	<b>-55 – 125 °C [ -67 – 257 °F ]</b>
Industry Standards	Glow Wire Rating	<b>Standard Part - Not Glow Wire</b>
	UL Rating	<b>Recognized</b>
	VDE Tested	<b>Yes</b>
	CSA Rating	<b>Certified</b>
	CSA File Number	<b>LR7189</b>
	Agency/Standard Number	<b>E28476</b>
	Agency/Standard	<b>CSA, UL</b>
Packaging Features	Packaging Method	<b>Bag</b>
	Packaging Quantity	<b>1400</b>

Product Compliance

[Statement of Compliance](#)  
PDF

[VIEW ALL PRODUCT COMPLIANCE](#)

# CUSTOMERS ALSO BOUGHT

RECTANGULAR POWER CONNECTORS	SINGLE PHASE FILTERS	RECTANGULAR POWER CONNECTORS	OCEAN APPLICATORS
			
<p>3P RCPT VAL-U-LOK SR V0 1586106-3</p>	<p>20VB6=F7354 S0 1-6609021-3</p>	<p>12P RCPT VAL-U-LOK V0 1-1586019-2</p>	<p>CRIMPER, INSULATION "F" (.140") 8-456134-2</p>
<p> Save to List  Find Similar Products</p>	<p> Save to List  Find Similar Products</p>	<p> Save to List  Find Similar Products</p>	<p> Save to List  Find Similar Products</p>