



MULTIPLE CONFIGURATION PCB CONNECTOR HOUSINGS



✓ Active

↓ **PRODUCT DRAWING**
English

↓ **3D PDF**

TE CONNECTIVITY (TE) 96P MOD2 ST-WANNE

AMPMODU | AMPMODU Headers

928034-4

TE Internal Number: 928034-4

Always EU RoHS/ELV Compliant

Connector Style **Receptacle**

Centerline **2.54 mm [.1 in]**

Row-to-Row Spacing **2.54 mm [.1 in]**

Number of Positions **96**

Number of Rows **3**

Product Drawings

96 POS. SHROUDED PIN HOUSING

PDF
English

CAD Files

Customer View Model

TIF
English

3D PDF

PDF
3D

Customer View Model

3D_IGS.ZIP
English

Customer View Model

3D_STP.ZIP
English

Customer View Model

2D_DXF.ZIP
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features

Connector Style	Receptacle
Row-to-Row Spacing	2.54 mm [.1 in]
PCB Mounting Orientation	Vertical
Shrouded	Yes
Connector Type	Housing

	Product Type	Connector
Configuration Features	Number of Positions	96
	Number of Rows	3
Contact Features	Contact Type	Socket
Mechanical Attachment	Mating Alignment Type	Polarizing Rib
	Mating Alignment	With
Housing Features	Centerline	2.54 mm [.1 in]
	Housing Material	PC, Polycarbonate GF
	Housing Color	Black
Dimensions	Height above PC Board	11.6 mm [.457 in]
Operation/Application	For Use With	RV 100 System
Other	Comment	According to DIN 41612, Type C

Product Compliance

[Statement of Compliance](#)
PDF

[VIEW ALL PRODUCT COMPLIANCE](#)