



928845-1 Product Details



928845-1

TE Internal Number: 928845-1

Active

Timer Contacts

Always EU RoHS/ELV Compliant (Statement of Compliance)

Product Highlights:

- Timer Products Product Line
- Standard Timer Series
- Wire-to-Board
- Applies To Wire/Cable
- Contact

[View all Features](#)

Quick Links

- ▶ [Pricing & Availability](#)
- ▶ [Search for Tooling](#)
- ▶ [Product Feature Selector](#)
- ▶ [Contact Us About This Product](#)

[Add to My Part List](#) [Request Sample](#) [Find Similar Products](#) [Buy Product](#)

Documentation & Additional Information	
Documents are temporarily unavailable. We are working hard to correct the problem. Please try again later.	<p>Additional Information:</p> <ul style="list-style-type: none"> • Product Line Information <p>Additional Product Images:</p> <ul style="list-style-type: none"> • Line Drawing <p>Related Products:</p> <ul style="list-style-type: none"> • Tooling

Product Features (Please use the Product Drawing for all design activity)	
<p>Product Type Features:</p> <ul style="list-style-type: none"> • Product Line = Timer Products • Product Type = Contact • Wire/Cable Type = Discrete Wire • Insulation Support = With <p>Termination Features:</p> <ul style="list-style-type: none"> • Wire/Cable Size (AWG) = 18 - 22 • Wire/Cable Size (mm²) = 0.34 - 0.88 • Termination Method to Wire/Cable = Crimp <p>Dimensions:</p> <ul style="list-style-type: none"> • Mating Area Interface Dimensions (mm [in]) = 3.18 x 0.81 [.125 x .032] <p>Contact Features:</p> <ul style="list-style-type: none"> • Contact Type = Socket • Contact Design = Standard Flat • Contact Base Material = CuZn30 • Contact Plating, Mating Area, Material = Pre-Tin <p>Configuration Features:</p> <ul style="list-style-type: none"> • GET 0.64 Connector System = No • Single Wire Sealing System = No 	<p>Industry Standards:</p> <ul style="list-style-type: none"> • RoHS/ELV Compliance = RoHS compliant, ELV compliant • Lead Free Solder Processes = Not relevant for lead free process • RoHS/ELV Compliance History = Always was RoHS compliant <p>Conditions for Usage:</p> <ul style="list-style-type: none"> • Applies To = Wire/Cable • Accepts Wire Insulation Diameter, Range (mm [in]) = 1.90 - 3.80 [0.075 - 0.150] <p>Operation/Application:</p> <ul style="list-style-type: none"> • Application Use = Wire-to-Board <p>Packaging Features:</p> <ul style="list-style-type: none"> • Packaging Method = Reel • Packaging Quantity = 2,500 <p>Other:</p> <ul style="list-style-type: none"> • Series = Standard Timer • Brand = AMP

Corporate Information

- [About TE](#)
- [Investors](#)
- [News Room](#)
- [Supplier Portal](#)
- [Careers](#)
- [Terms & Conditions](#)
- [Privacy Policy](#)
- [AODA Accessibility Policy](#)
- [AODA Multi-Year Accessibility Plan](#)

Quick Links

- [Distributor Inventory](#)
- [Product Cross Reference](#)
- [Documents & Drawings](#)
- [Product Compliance Support Center](#)
- [Site Map](#)

Customer Support

- [Email or Chat With Us](#)
- [Find a Phone Number](#)
- [Knowledge Base](#)
- [Manage Your Account](#)

Keep Me Informed



