


## HEAT SHRINK TUBING



✓ Active

TE CONNECTIVITY

### HTAT-8/2-0-SP

[Raychem](#) | [HTAT](#)

HTAT-8/2-0-SP

TE Internal Number: 1586404002

Alias ID: 1191146-9

[Always EU RoHS/ELV Compliant](#)

Wall Type **Dual**

Resistant To **Fluids, Mechanical Damage, Strain**

Low Outgassing **No**

Product Source **Czech Republic**

Packaging Method **Spool**

## Catalog Pages/Data Sheets

[HTAT Pages From 9-1773447-9](#)

PDF  
**English**

## Product Specifications

Product Specification

[HTAT Sleeving](#)

PDF  
**English**

Please review product documents or [contact us](#) for the latest agency approval information.

### Product Type Features

Wall Type

**Dual**

Product Family

**HTAT**

### Electrical Characteristics

Voltage (Max) (kV)

**.6**

### Body Features

Shrink Ratio

**4:1**

Color

**Black**

Flexibility

**Semi-Flexible**

Material

**Irradiated Modified Polyolefin**

Fluid Type

**Diesel Fuel, Hydraulic Fluid, Lubricating Oil, Water**

### Dimensions

Recovered Inside Diameter (Max)

**2 mm [ .079 in ]**

Recovered Wall Thickness (Tolerance)

**1 mm [ .0391 in ]**

	Expanded Inside Diameter (Min)	8 mm [ .315 in ]
Usage Conditions	Resistant To	Fluids, Mechanical Damage, Strain
	Recovery Temperature (°C)	110
	Operating Temperature Range (°C)	-55 – 125
	Flammability	Flame-Retardant
	Fluid Resistance	Moisture/Spray Protection, Splash Protection
	Shrink Temperature (Min) (°C)	90
Product Availability	Applicable Region	Global
Packaging Features	Packaging Method	Spool
Other	Low Outgassing	No
	Product Source	Czech Republic
Product Compliance	<a href="#">Statement of Compliance</a> PDF	
	<a href="#">VIEW ALL PRODUCT COMPLIANCE</a>	