



W58-XB1A4A-4 Product Details

[Share](#) [Print](#) [Email](#)



W58-XB1A4A-4
(1-1393249-8)

TE Internal Number: 1-1393249-8

Active

[View 3D PDF](#)

Thermal Circuit Breakers

Converted to EU RoHS but not ELV Compliant (Statement of Compliance)

Product Highlights:

- Circuit Breaker
- W58 Series
- 1 Poles
- Actuator Style = Push to Reset
- Current Rating = 4 A

[View all Features](#)

Quick Links

- ▶ [Pricing & Availability](#)
- ▶ [Search for Tooling](#)
- ▶ [Product Feature Selector](#)
- ▶ [Contact Us About This Product](#)

[Add to My Part List](#) [Request Sample](#) [Find Similar Products](#) [Buy Product](#)

Documentation & Additional Information

Product Drawings:

- None Available

Catalog Pages/Data Sheets:

- [W58 Push To Reset Only Thermal Circuit Breaker \(PDF, English\)](#)
- [Flyer - UL1500 Ignition Protected Circuit Breakers \(PDF, English\)](#)

Product Specifications:

- None Available

Application Specifications:

- None Available

Instruction Sheets:

- None Available

CAD Files: (CAD Format & Compression Information)

- [2D Drawing \(DXF, Version J\)](#)
- [3D Model \(IGES, Version J\)](#)
- [3D Model \(STEP, Version J\)](#)

[List all Documents](#)

Additional Information:

- [Product Line Information](#)

Related Products:

- [Tooling](#)

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- [Product Type](#) = Circuit Breaker
- [Actuator Style](#) = Push to Reset

Mechanical Attachment:

- [Mounting Options](#) = Knurled Nut/Hex Nut
- [Mounting Bushing](#) = 7/16" x .500" [12.70 mm] Long

Electrical Characteristics:

- [Current Rating \(A\)](#) = 4
- [Operating Voltage, Max.](#) = 50 VDC, 250 VAC
- [Interrupt Capacity](#) = 2,000 A @ 50 VDC or 1,000 A @ 250 VAC

Termination Features:

- [Termination Type](#) = 6.35 [.250] Straight Quick Connect Tab

Body Features:

- [Button Color](#) = White with Red Rate Marking, Red Trip Band

Contact Features:

- [Number of Poles](#) = 1
- [Trip Time at 200%](#) = 10 to 45 Seconds

Configuration Features:

- [Circuit Function](#) = Series Trip

Industry Standards:

- [RoHS/ELV Compliance](#) = RoHS/Not ELV Compliant
- [Lead Free Solder Processes](#) = Not relevant for lead free process
- [RoHS/ELV Compliance History](#) = Converted to comply with RoHS not ELV directives
- [Approved Standards](#) = CSA Certified

Packaging Features:

- [Mounting Hardware Packaging](#) = Assembled to Bushing

Other:

- [Series](#) = W58
- [Brand](#) = Potter & Brumfield

[News Room](#)

[Supplier Portal](#)

[Careers](#)

[Terms & Conditions](#)

[Privacy Policy](#)

[AODA Accessibility Policy](#)

[AODA Multi-Year Accessibility
Plan](#)

[Documents & Drawings](#)

[Product Compliance Support Center](#)

[Site Map](#)

[Knowledge Base](#)

[Manage Your Account](#)

